


# Microphone Cable Club Series MKII; 2 x 0,34 mm<sup>2</sup>; PVC Ø 6,50 mm; black

Art. No.: 200-0051NE

ANALOG

OFC



## General Data

Article number :	200-0051NE
Name :	Club Series MKII
EAN :	4049371001939
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Microphone Cable
Colour :	black
BPVo-Euroclass :	Fca

## Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,34mm <sup>2</sup> )CY
Jacket material :	PVC
Jacket Ø [mm] :	6,50
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm <sup>2</sup> ] :	0,34
Inner conductor Ø (audio) [mm] :	0,66
AWG (audio) :	22
Shielding :	Copper braided shielding with 0.10 mm indiv. strands
Shielding factor [%] :	95
Copper strands (audio) :	19
Copper strand Ø (audio) [mm] :	0,15
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,50
Weight per 1 m [g] :	50
UV-resistant :	yes
Fire load per m [kWh] :	0,22
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	6,5
Height [mm] :	6,5

Capac. cond./cond. per 1 m (audio) [pF] :	58
Capac. cond./shield. per 1 m (audio) [pF] :	115
Impedance [Ω] :	100
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	55
Shield. resistance per 1 km [Ω] :	25

## Electrical Data