

Microphone cable Tempoflex Microphone; 2 x 0.34 mm²; TPE Ø 7.30 mm; black, AES/EBU compatible, heat resistant up to +110°C, with ARAMID strain relief

Art. No.: 200-0051T



General Data

| | |
|--------------------|-------------------------|
| Article number : | 200-0051T |
| Name : | Tempoflex Microphone |
| EAN : | 4049371003551 |
| Properties : | Digital 110 Ω AES / EBU |
| Properties : | Analog |
| Properties : | Halogen-free / LSZH |
| Properties : | OFC oxygen free copper |
| Application area : | Stage / live |
| Application area : | Mobile outdoor / indoor |
| Application area : | Installation |
| Application area : | ELA 100 V |
| Application : | Microphone Cable |
| Colour : | black |
| BPVo-Euroclass : | Fca |

Technical Data

| | |
|--|---|
| Signal transmission : | symmetrical |
| Construction : | (2LI2X0,34mm ² +2(ZN)2X)18Y C18YC |
| Jacket material : | TPE |
| Jacket Ø [mm] : | 7,30 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 2 |
| Inner conductor (audio) [mm ²] : | 0,34 |
| Inner conductor Ø (audio) [mm] : | 0,66 |
| AWG (audio) : | 22 |
| Shielding : | Copper braiding shield., tinned, with 0.10 mm indiv. strand |
| Shielding factor [%] : | 95 |
| Copper strands (audio) : | 42 |
| Copper strand Ø (audio) [mm] : | 0,10 |
| Conductor insulation material : | Cross linked Polyolefin |
| Weight per 1 m [g] : | 59 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,45 |
| Style variant : | round |
| Packing : | 100 m spool |
| Packing : | 500 m spool |
| Temperature min. [°C] : | -20 |
| Temperature max. [°C] : | 110 |
| Width [mm] : | 7,3 |
| Height [mm] : | 7,3 |



Electrical Data

| | |
|---|-----|
| Capac. cond./cond. per 1 m (audio) [pF] : | 50 |
| Capac. cond./shield. per 1 m (audio) [pF] : | 90 |
| Impedance [Ω] : | 110 |
| Insulation resist. per 1 km [GΩ] : | 1 |
| Insulation resist. per 1 km (audio) [GΩ] : | 1 |
| Conductor resistance per 1 km [Ω] : | 62 |
| Shield. resistance per 1 km [Ω] : | 14 |