

Microphone Cable SC-Primus; 2 x 0,50 mm²; PVC Ø 6,50 mm; blue

Art. No.: 200-0152

ANALOG

OFC



General Data

Article number :	200-0152
Name :	SC-Primus
EAN :	4049371001977
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Microphone Cable
Colour :	blue
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,50mm ²)(ST)DY
Jacket material :	PVC
Jacket Ø [mm] :	6,50
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,50
Inner conductor Ø (audio) [mm] :	0,80
AWG (audio) :	20
Shielding :	Copper spiral sleeve tin-plated + metallic fleece
Shielding factor [%] :	100
Copper strands (audio) :	28
Copper strand Ø (audio) [mm] :	0,15
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,65
Weight per 1 m [g] :	53
Fire load per m [kWh] :	0,23
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	6,5
Height [mm] :	6,5

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	80
---	----

Capac. cond./shield. per 1 m (audio) [pF] :	145
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	37
Shield. resistance per 1 km [Ω] :	27