


Patch & Microphone Cable SC-Scuba 14; 2 x 0,14 mm²; PVC Ø 3,80 mm; grey

Art. No.: 200-0316

ANALOG

OFC



General Data

| | |
|--------------------|--------------------------|
| Article number : | 200-0316 |
| Name : | SC-Scuba 14 |
| EAN : | 4049371002035 |
| Properties : | Analog |
| Properties : | OFC oxygen free copper |
| Application area : | Studio / Broadcast |
| Application : | Patch & Microphone Cable |
| Colour : | grey |
| BPVo-Euroclass : | Fca |

| | |
|-------------------------------------|-----|
| Conductor resistance per 1 km [Ω] : | 135 |
|-------------------------------------|-----|

| | |
|-----------------------------------|----|
| Shield. resistance per 1 km [Ω] : | 30 |
|-----------------------------------|----|

Technical Data

| | |
|--|---|
| Signal transmission : | symmetrical |
| Construction : | (2LI2Y0,14mm ²)CY |
| Jacket material : | PVC |
| Jacket Ø [mm] : | 3,80 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 2 |
| Inner conductor (audio) [mm ²] : | 0,14 |
| Inner conductor Ø (audio) [mm] : | 0,42 |
| AWG (audio) : | 26 |
| Shielding : | Copper braiding shield., tin-plated, with 0.10 mm indiv. strand |
| Shielding factor [%] : | 90 |
| Copper strands (audio) : | 18 |
| Copper strand Ø (audio) [mm] : | 0,10 |
| Conductor insulation material : | PE |
| Conductor insulation Ø [mm] : | 1,15 |
| Weight per 1 m [g] : | 25 |
| Fire load per m [kWh] : | 0,09 |
| Style variant : | round |
| Packing : | 100 m spool |
| Packing : | 500 m spool |
| Temperature min. [°C] : | -25 |
| Temperature max. [°C] : | 70 |
| Width [mm] : | 3,8 |
| Height [mm] : | 3,8 |

Electrical Data

| | |
|---|-----|
| Capac. cond./cond. per 1 m (audio) [pF] : | 65 |
| Capac. cond./shield. per 1 m (audio) [pF] : | 130 |
| Impedance [Ω] : | 100 |
| Insulation resist. per 1 km [GΩ] : | 1 |
| Insulation resist. per 1 km (audio) [GΩ] : | 1 |