


Patch cable SC-Isopod SO-F22; 2 x 0,22 mm²; PVC Ø 3,30 mm; black Art. No.: 200-0401

ANALOG

OFC



General Data

| | |
|--------------------|------------------------|
| Article number : | 200-0401 |
| Name : | SC-Isopod SO-F22 |
| EAN : | 4049371004480 |
| Properties : | Analog |
| Properties : | OFC oxygen free copper |
| Application area : | Installation |
| Application : | Patch cable |
| Colour : | black |
| BPVo-Euroclass : | Fca |

Technical Data

| | |
|--|---|
| Signal transmission : | symmetrical |
| Construction : | (2LI2Y0,22mm ²)(ST)Y |
| Jacket material : | PVC |
| Jacket Ø [mm] : | 3,30 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 2 |
| Inner conductor (audio) [mm ²] : | 0,22 |
| Inner conductor Ø (audio) [mm] : | 0,53 |
| AWG (audio) : | 24 |
| Shielding : | AL / PT foil + AL / PT foil + filler strand, tin-plated |
| Shielding factor [%] : | 100 |
| Copper strands (audio) : | 7 |
| Copper strand Ø (audio) [mm] : | 0,20 |
| Conductor insulation material : | PE |
| Conductor insulation Ø [mm] : | 1,12 |
| Weight per 1 m [g] : | 16 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,05 |
| Style variant : | round |
| Packing : | 200 m spool |
| Temperature min. [°C] : | -25 |
| Temperature max. [°C] : | 70 |
| Width [mm] : | 3,3 |
| Height [mm] : | 3,3 |

Electrical Data

| | |
|---|-----|
| Capac. cond./cond. per 1 m (audio) [pF] : | 74 |
| Capac. cond./shield. per 1 m (audio) [pF] : | 143 |
| Insulation resist. per 1 km [GΩ] : | 0,2 |
| Insulation resist. per 1 km (audio) [GΩ] : | 0,2 |
| Conductor resistance per 1 km [Ω] : | 88 |

Shield. resistance per 1 km [Ω] :

75