

Patch & Microphone Cable SC-Cicada SO-D14; 2 x 0,14 mm²; PUR Master-Blend Ø 2,60 mm; black

Art. No.: **200-0451**

ANALOG **OFC** **PUR**



General Data

Article number :	200-0451
Name :	SC-Cicada SO-D14
EAN :	4049371002066
Properties :	Analog
Properties :	PUR
Properties :	OFC oxygen free copper
Application area :	Installation
Application :	Patch & Microphone Cable
Colour :	black
BPVo-Euroclass :	Fca

Conductor resistance per 1 km [Ω] : 148

Shield. resistance per 1 km [Ω] : 30

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,14mm ²)DY
Jacket material :	PUR Master-Blend
Jacket Ø [mm] :	2,60
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,14
Inner conductor Ø (audio) [mm] :	0,42
AWG (audio) :	26
Shielding :	Copper spiral shielding + filler strand, tin-plated (0.22 mm ²)
Shielding factor [%] :	95
Copper strands (audio) :	18
Copper strand Ø (audio) [mm] :	0,10
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	0,90
Weight per 1 m [g] :	13
UV-resistant :	yes
Fire load per m [kWh] :	0,08
Style variant :	round
Packing :	100 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	2,6
Height [mm] :	2,6

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	65
Capac. cond./shield. per 1 m (audio) [pF] :	120
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (audio) [GΩ] :	1