


# Microphone Cable SC-Symbiotic 3; 3 x 0,20 mm<sup>2</sup>; TPE Ø 5,20 mm; black

Art. No.: 200-0601H3

ANALOG

OFC



## General Data

Article number :	200-0601H3
Name :	SC-Symbiotic 3
EAN :	4049371004596
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application :	Microphone Cable
Colour :	black
BPVo-Euroclass :	Fca

## Technical Data

Signal transmission :	symmetrical
Construction :	(3LI2Y0,20mm <sup>2</sup> )YDDY
Jacket material :	TPE
Jacket Ø [mm] :	5,20
Number of Channels (audio) :	1
Inner conductor (audio) :	3
Inner conductor (audio) [mm <sup>2</sup> ] :	0,20
Inner conductor Ø (audio) [mm] :	0,50
AWG (audio) :	24
Shielding :	Double copper spiral, counter-rotating
Shielding factor [%] :	100
Copper strands (audio) :	102
Copper strand Ø (audio) [mm] :	0,05
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,30
Weight per 1 m [g] :	38
UV-resistant :	yes
Fire load per m [kWh] :	0,11
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	5,2
Height [mm] :	5,2

## Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	95
Capac. cond./shield. per 1 m (audio) [pF] :	130

Insulation resist. per 1 km [GΩ] :	0,2
Insulation resist. per 1 km (audio) [GΩ] :	0,2
Conductor resistance per 1 km [Ω] :	94
Shield. resistance per 1 km [Ω] :	25