

Speaker Cable Elephant Robust SPM840 CPR; 8 x 4,00 mm²; FRNC Ø 16,40 mm; black; Cca Art. No.: 490-0051-840FC

ANALOG **FRNC** **HALOGEN-FREE** **OFC**



General Data

Article number :	490-0051-840FC
Name :	Elephant Robust SPM840 CPR
EAN :	4049371403658
Properties :	OFC oxygen free copper
Properties :	FRNC flame retardant
Properties :	Halogen-free / LSZH
Properties :	Analog
Application area :	ELA 100 V
Application area :	Installation
Application :	Speaker Cable
Colour :	black
BPVo-Euroclass :	Cca

Technical Data

Construction :	(8LIY4,0mm ²)Y
Jacket material :	FRNC
Jacket Ø [mm] :	16,40
Number of Channels (audio) :	1
Inner conductor (audio) :	8
Inner conductor (audio) [mm ²] :	4,00
Inner conductor Ø (audio) [mm] :	2,26
AWG (audio) :	11
Copper strands (audio) :	48
Copper strand Ø (audio) [mm] :	0,31
Conductor insulation Ø [mm] :	4,00
Weight per 1 m [g] :	485
UV-resistant :	yes
Fire load per m [kWh] :	2,25
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-40
Temperature max. [°C] :	85
Width [mm] :	16,4
Height [mm] :	16,4

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	95
Surge impedance (audio) [Ω] :	52
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	4,5
Test voltage [V] :	2000