

DMX Binary 234 AES/EBU MKII; 2 x 0,34 mm²; PUR Ø 6,20 mm; black

Art. No.: 521-0051

ANALOG

DIGITAL

OFC



General Data

Article number :	521-0051
Name :	Binary 234 AES/EBU MKII
EAN :	4049371002370
Properties :	Analog
Properties :	PUR Master Blend
Properties :	OFC oxygen free copper
Properties :	Digital 110 Ω AES / EBU
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	DMX
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,34mm ²)(ST)DY
Jacket material :	PUR
Jacket Ø [mm] :	6,20
Number of Channels (AES/EBU, DMX) :	1
Inner conductor (AES/EBU, DMX) :	2
Inner conductor (AES/EBU, DMX) [mm ²] :	0,34
Inner conductor Ø (AES/EBU, DMX) [mm] :	0,66
AWG (AES/EBU, DMX) :	22
Shielding :	Copper spiral shielding + aluminum steamed fleece
Shielding factor [%] :	100
Copper strands (AES/EBU, DMX) :	19
Copper strand Ø (AES/EBU, DMX) [mm] :	0,15
Conductor insulation material :	Foam / Skin-PE
Conductor insulation Ø [mm] :	1,50
Weight per 1 m [g] :	50
UV-resistant :	yes
Fire load per m [kWh] :	0,17
Style variant :	round
Packing :	100 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	6,2
[mm] :	6,2

Electrical Data

Capac. cond./cond. per 1 m (AES/EBU, DMX) [pF] :	63
Capac. cond./shield. per 1 m (AES/EBU, DMX) [pF] :	115
Impedance [Ω] :	110
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (AES/EBU, DMX) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	53
Shield. resistance per 1 km [Ω] :	28