

## NF-Phono cable SC-Aquila Control; 4 x 0,14 mm<sup>2</sup>; 2 x 0.14 mm<sup>2</sup>; PVC; blue

Art. No.: 800-0152

ANALOG

OFC



### General Data

|                    |                        |
|--------------------|------------------------|
| Article number :   | 800-0152               |
| Name :             | SC-Aquila Control      |
| EAN :              | 4049371003230          |
| Properties :       | Analog                 |
| Properties :       | OFC oxygen free copper |
| Application area : | Studio / Broadcast     |
| Application :      | NF-Phono cable         |
| Colour :           | blue                   |
| BPVo-Euroclass :   | Fca                    |

### Technical Data

|   |                                  |
|---|----------------------------------|
| Signal transmission :                           | asymmetrical                     |
| Jacket material :                               | PVC                              |
| Number of Channels (audio) :                    | 1                                |
| Number of Channels (control) :                  | 2                                |
| Inner conductor (audio) :                       | 4                                |
| Inner conductor (audio) [mm <sup>2</sup> ] :    | 0,14                             |
| Inner conductors (control) [mm <sup>2</sup> ] : | 0,14                             |
| AWG (audio) :                                   | 26                               |
| AWG (control) :                                 | 26                               |
| Shielding :                                     | Copper braiding + Polyester foil |
| Copper strands (audio) :                        | 18                               |
| Copper strands (control) :                      | 18                               |
| Copper strand Ø (audio) [mm] :                  | 0,10                             |
| Copper strand Ø (control) [mm] :                | 0,10                             |
| Conductor insulation material :                 | PE                               |
| Conductor insulation Ø [mm] :                   | 2,20                             |
| Weight per 1 m [g] :                            | 124                              |
| Fire load per m [kWh] :                         | 0,44                             |
| Style variant :                                 | twin                             |
| Packing :                                       | 50m spool                        |
| Temperature min. [°C] :                         | -20                              |
| Temperature max. [°C] :                         | 70                               |
| Width [mm] :                                    | 21                               |
| Height [mm] :                                   | 4,5                              |

### Electrical Data

|   |      |
|---|------|
| Capac. cond./shield. per 1 m (audio) [pF] :         | 60   |
| Capacity wire/electic screen at 1m (control) [pF] : | 60   |
| Insulation resist. per 1 km [GΩ] :                  | 0,01 |
| Insulation resist. per 1 km (audio) [GΩ] :          | 0,01 |
| Insulation resist. per 1 km (control) [GΩ] :        | 0,01 |

Conductor resistance per 1 km [Ω] :

149