VIEW™ | **Professional Amplifier**

AMP2200 - Professional Amplifier

The VIEW Professional Amplifier is the ideal product when more power is required. The AMP2200 provides 200 watts per channel or 600 watts bridged. The VIEW Professional Amplifier can be used in conjunction with ClearOne products or with third party systems.

ClearOne.

PROFESSIONAL

AMPLIFIER



APPLICATIONS

- + Conferencing
- + Multi-zone Paging
- + Emergency Communications
- + Business Entertainment
- + Sound Reinforcement

ADVANTAGES

- + The onboard EIM port allows connection directly to ClearOne devices with an EIM connection. By using a CAT5 connection, the AMP2200 makes it easy to add an external amplifier to any VIEW system.
- + The AMP220 is designed to be freestanding or rack mounted. It occupies 1RU of space on a standard 19" rack.
- + Uses a forced air tunnel fan system to cool the amplifier at very low ambient noise levels.
- + Includes LED lights that indicates power state and activity, including clipping. It will also indicate when a fault condition exists like overheating, a hard clip, or a short in the wires.
- + Ships with rack ears for easy rack mounting.

The Power of AV over IP™

ClearOne.

> VIEW REAR PANEL



> SPECIFICATIONS

1V-RMS Input Two (2) 290W+290W (4Ω) 200W+ 200W (8Ω) 600W (8Ω Bridge)

Frequency Response 20 - 20,000Hz

Distortion >0.05%

Input Sensitivity +4dB

Input Impedance $44k\Omega$ Balanced $22k\Omega$ Unbalanced

Damping Factor 300

Hum & Noise -102dB

Crosstalk >60dB

Input Connectors XLR/TRS Phone / EIM

Output Connectors 5-Way Binding Post / EIM

Cooling 2 Speed DC Fan

Power Consumption 4.2 A @ 120 VAC

Protection DC Fault

On/Off Muting Short Circuit Overload **Dimensions (W x H x D)** 19" x 1.75" x 15.25" 48.3 cm x 4.4 cm x 46.5 cm

Weight 25 lbs (11.9kg)

Compliance Restriction of use of certain Hazardous Substances (RoHS) Compliant

Part Number AMP2200

Powered by StreamNet™

> CLEARONE LOCATIONS

Headquarters: Salt Lake City, UT USA 5225 Wiley Post Way Suite 500 Salt Lake City, UT 84116 Tel: 801-975-7200 Toll Free: 800-945-7730 Fax: 801-977-0087 sales@clearone.com Latin America Tel: 801-974-3621 global@clearone.com EMEA Tel: 44 (0) 1189 036 053 global@clearone.com APAC Tel: 801-303-3388 global@clearone.com

© 2010 ClearOne. All rights reserved. Other product names may be trademarks of their respective owners. Information in this document subject to change without notice. 802-000-031-DS Rev. 1.0. May 2010.