

HIGH POWER / SPEAKERS / ASSETS

ASB-880U

ACTIVE HIGH-POWER LOUDSPEAKER.



CLASS D



RADIO



SD



USB

- ✓ Great power and sound quality.
- ✓ USB/SD player with remote control.
- ✓ Woofer protected by front metal grille.
- ✓ Carrying handles, suspension points, legs for floor support and shape of monitor.



+ Info:
<https://fonestar.com/ASB-880U>

ESPECIALLY RECOMMENDED IN:



Sports facilities



Hospitality



Hotels



All sectors

DESCRIPTION

Fonestar has developed the range of active high-power speakers ASB, the most affordable range of active speakers, which provide great sound quality and integrate all the necessary elements of a professional sound installation. It has microphone, line input, wireless receiver, USB/SD player, mixer, speaker and amplifier. A wide range of playback options and audio inputs make it highly versatile and adaptable. Class D amplifier with high efficiency and high reliability thanks to low maintenance protection circuits. Robust injection structure, high transport resistance. Audio inputs with standard connectors: XLR, jack and RCA. Powerful, distortion-free sound that provides a precise playback of your music. Passive speaker output with speaker connector. Remote control is possible thanks to the remote control. Its simple and intuitive use minimizes setup time depending on the installation. Suspension points and hole in the base for 35 mm tube for suspended or bracket installation, and feet for floor installation. Front metal grille ensures speaker integrity. Perfect for pubs, gyms, restaurants, small events, children's parties,

TECHNICAL CHARACTERISTICS

FEATURES	Active loudspeaker with extra resistant PP injection box. Wireless receiver and USB/SD player with remote control. Output for passive loudspeaker. Woofer protected by front metal grille. Carrying handles, suspension points, floor feet and monitor shape. Hole in the base for 35 mm tube.
AMPLIFIER	160 W maximum, 80 W RMS Bass: 100 W maximum, 50 W RMS Treble: 60 W maximum, 30 W RMS
PROTECTION	3 protection circuits: short circuit, surge and temperature
LOUDSPEAKERS	1 x 8" woofer 1 compression driver: 1" diaphragm
RESPONSE	60-18,000 Hz
INPUTS	1 balanced mic., XLR and 6.3 mm jack 1 aux line, XLR and 2 x RCA
OUTPUTS	1 balanced line, 6.3 mm jack (TRS) mono signal 1 amplified for passive loudspeaker, 8 Ohm loudspeaker connector
INDICATORS	Operation on the front. Power and peak on the rear panel



+ Info:
<https://fonestar.com/ASB-880U>

CONTROLS	Input volume and general volume USB/SD player control Bass and treble control
SUSPENSION POINTS	4 M8 points
POWER SUPPLY	230 V AC, 120 W 115 V AC on request
DIMENSIONS	260 x 420 x 230 mm depth
WEIGHT	7.1 kg



+ Info:

<https://fonestar.com/ASB-880U>