

VIEW[™] ANTHOLOGY[™]

Light Commercial Media Server

ANTHOLOGY simplifies access to audio sources located randomly across a network or anywhere online by automatically finding, indexing and playing Internet radio, music services and network or local audio files. Easily create the perfect atmosphere across your commercial StreamNet[™] AV system.







Hospitality and Entertainment Venues

Retail establishments

Houses of Worship







Powered by StreamNet™

Features

- + Full integration with StreamNet AV distribution system
- + Access to thousands of online music sources and streaming content services including TuneIn*
- + Support for Windows Media, iTunes (AAC), MP3, FLAC, WAV and all popular audio formats.
- + Automatic discovery and indexing of network media files
- + 1 TB local storage for up to 200,000 songs
- + Centralized access to full audio collection
- + Support for up to four simultaneous digital streams, plus one local output
- + Multiple units can be linked and controlled from the same touch/control panel or Flash-enabled mobile devices
- + Playlist customization across any combination of zones
- + Control with StreamNet touch panels or mobile devices through browser-based interface
- + Scheduling for pre-programmed content with a single command
- + Control imagery for basic, digital signage capabilities

*Find all DRM licensing information in the ClearOne Digital Media Guide pages 26 – 30



ANTHOLOGY BACK PANEL



Functional Specifications

AUDIO

 Stream Music - Play music from network shares, 4 streams plus one, local output

 Online music services - TuneIn

 iTunes - Synchronized

 Windows Media Player - Synchronized

 CD RIP - Audio sync

 Browse - Music and control playback from browsers

 Pre-Amp output - 1 preamp output for theater or MediaLinX MLAV

VIDEO

Video Output - 1 DVI/VGA output for "now playing" and OSD (On-Screen Display) Image Slideshow - Displays images from folder

POWER

Power Consumption < 20W

CONNECTIONS

10/100/100 Mbps Ethernet 3x USB 3.5mm Analog Audio Output VGA, DVI-D 28V Phoenix-style power input

WEIGHT

7.73 lbs (3.5 kg)

MECHANICAL

17.32" x 1.73" x 8.66" (W x H x D) (440mm x 44mm x 220mm); 7.73 lbs (3.5 kg)

ENVIRONMENTAL

Operating Temperature: 32° - 104° F (0° - 40° C), Relative Humidity: 0 to 90%

INTERFACES

StreamNet-integrated touch panel Browser-based Flash application on PC and smartphones Browser based configuration tool

COMPLIANCE

RoHS Compliant. WEEE, China RoHS, EU Reach, EIA 571, EN 55022/ICES-003/FCC

PART NUMBER

VIEW 910-225-031



North America Tel: 801-975-7200 Toll Free: 800-945-7730 Sales: 800-707-6994 Fax: 801-977-0087 sales@clearone.com Europe & Oceania Tel: +44 (0) 1189 036 053 global@clearone.com Asia Pacific Tel: +852 3590 4526 global@clearone.com Latin America Tel: 801-974-3621 global@clearone.com Middle East Tel: +852 3590 4526 global@clearone.com

Other product names may be registered trademarks of their respective owners who do not necessarily endorse ClearOne or ClearOne's products. All rights reserved. Information in this document subject to change without notice. © 2012 ClearOne. 802-000-100-19 Revision 1.0 March 2012.