

HDMI Distributor, OHD14 / OHD18



Descriptions

OpticIS new HDMI Distributor, OHD 14 or OHD18 makes one(1) HDMI video source split into four(4) or eight(8) displays, simultaneously without any signal loss or digital noise. It guarantees to support full channels .HDMI 1.3/HDCP1.1 compliant.

Key Features

- Offers many types of option for **EDID** (OHD14)
- Supports **DDC/HDCP**
- CEC function
- Supports up to **WUXGA (1920x1200)**, at 60Hz and HD 1080i/p (1920x1080).
- Provides status LED indicators.
- Compatible with HDMI-DVI cable.

Technical Features

Model Name	OHD14	OHD18
Resolution	VGA to WUXGA , 480p to 1080i/p	
Input TMDs Signal	1.2V	
Input DDC Signal	5V	
Power Supply	DC +5V , 2.6A	DC +5V ,6.0A
Dimension(mm)	200 x 104 x 25	436 x 120 x 44
Weight(kg)	0.28	0.68
Operating Temp.	0℃~40℃	
Storage Temp.	-20℃ ~60℃	
Operating Humidity	30%~80%	
Storage Humidity	60%	
Power Consumption	5.5W	18W

OPTICIS HQ

OpticIS Co., Ltd.
304, Byucksan Technopia, 434-6
Sangdaewon-Dong, Chungwon-Ku,
Sungnam City, Kyungki-Do, 462-716
South Korea
Tel: +82 (31) 737-8033~8
Fax: +82 (31) 737-8079
www.opticis.com
tosales@opticis.com