

# Power Supply for CALICO | PRO

C7-PRO-400RPS



## Overview

The C7-PRO-400RPS is a hot swappable redundant power supply for CALICO and is designed for mission critical applications. It operates in conjunction with the identical chassis PSU on a load balanced basis and provides seamless and uninterrupted fail-over should the chassis PSU fail or vice versa.

## Features

Hot-Swappable redundant PSU

## Designed For

C7-PRO CALICO (2U) models

## Max Installable

C7-PRO-2200	2 (one is already pre-fitted)
-------------	-------------------------------

## Installation

Hot-swappable redundant power supply	Load balancing type
--------------------------------------	---------------------

## Warranty

Limited warranty	5 years parts and labor**
------------------	---------------------------

MTBF	200,000 hours
------	---------------

Designed for continuous use	24/7, 365 days a year operation, with 5-year limited warranty. Perfect for mission critical applications
-----------------------------	--

## Regulatory Compliance

Power supply	FCC, CE, RoHS, UL, TUV, CCC
--------------	-----------------------------

## Environmental

Operating Temperature	32° to 104°F (0° to +40°C)
-----------------------	----------------------------

Operating Humidity	10% to 85%, Non-condensing
--------------------	----------------------------

Storage Temperature	14° to +158°F (-10° to +70°C)
---------------------	-------------------------------

Storage Humidity	10% to 85%, Non-condensing
------------------	----------------------------

## Mechanical

Height	40mm (1.57")
--------	--------------

Width	54.5mm (2.15")
-------	----------------

Depth	PSU casing - 220mm (8.66") / including removal handle 247mm (9.72")
-------	---

Weight	780g
--------	------

## Power

Input voltage	100 to 240V (+/- 10%) AC (50/60Hz), 6.3A auto detecting
---------------	---

Output voltage	12V dc
----------------	--------

Power	400W
-------	------

\*\* Must be installed by a skilled professional