

# Quad HDMI 4K Input Module for CALICO | PRO

C7-PRO-HDMI-4K4IN



## Overview

This high bandwidth module adds four HDMI 2.0, HDCP 2.2 inputs, supporting up to 4K60

## Features

Quad HDMI 2.0 inputs	4x 2160p (4096x2160) 60Hz
HDCP 2.2	Yes

## Designed For

C7-PRO CALICO models with input expansion slots	Input expansion module for CALICO models only
---	---

## Max Installable

C7-PRO-2200	1 module
-------------	----------

## Installation

Field upgradable expansion module	Can be fitted in to slot 12 only
Caution *	To install or replace the unit has to be powered down and disconnected from the supply. Observe static safety precautions when handling the module.**

## Video Inputs

HDMI 2.0	4x 2160p (4096x2160) 60Hz
HDCP	2.2 / 1.4
Chroma sub-sampling (10-bit)	4:2:2
Chroma sub-sampling (8-bit)	4:4:4
Color space	YCbCr BT.601, YCbCr BT.709, RGB, RGB limited range and auto detect
De-interlacer	Yes

## Supported Input Resolutions

720p (1280x720)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz
1080i (1920x1080)	50, 59.94, 60Hz
1080p (1920x1080)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60, 100, 119.88, 120Hz
2160p (3840x2160)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz
2160p (4096x2160)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz

\* This item is not hot-swappable  
 \*\* Must be installed by a skilled professional

## Audio

Supported sampling rate	48kHz
Sample size	24 bits
Supported channels	One stereo pair per input

## Warranty

Limited warranty	5 years parts and labor**
------------------	---------------------------

## Regulatory Compliance

System / modules	FCC, CE, RoHS, UL, UKCA
------------------	-------------------------

## Environmental

Operating temperature	32° to 104°F (0° to +40°C)
Operating humidity	10% to 85%, Non-condensing
Storage temperature	14° to +158°F (-10° to +70°C)
Storage humidity	10% to 85%, Non-condensing

## Power

Powered by the CALICO main unit