

# Quad HDMI Output Module for CALICO | PRO

C7-PRO-HDMI-4K4OUT



Overview	
4x HDMI video outputs supporting up to 4K60	
Features	
Quad HDMI 2.0 4K60 output module	4x 2160p (3840x2160) 60Hz
HDCP 2.2	
Designed For	
C7-PRO CALICO Models with output expansion slots	High bandwidth output expansion module for CALICO models only
Max Installable	
C7-PRO-2200	1 module
Installation	
Field upgradable expansion module	Can be fitted in to slot 10 only
Caution *	To install or replace the unit has to be powered down and disconnected from the supply. Observe static safety precautions when handling the module.**

Video Outputs	
HDMI	4x independent outputs
HDCP	2.2 / 1.4
Chroma sub-sampling	4:4:4 (8-bit) 4:2:2 (10-bit)
Color Depth	10-bit
Color Space	YCbCr BT.601, YCbCr BT.709, RGB, RGB limited range and auto detect
Supported Output Resolutions	
720p (1280x720)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz
1080i (1920x1080)	50, 59.94, 60Hz
1080p (1920x1080)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60, 100, 119.88, 120Hz
2160p (3840x2160)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz
Audio	
Supported sampling rate	48kHz
Sample size	24 bits

Warranty	
Limited warranty	5 years parts and labor**
Regulatory Compliance	
System / modules	FCC, CE, RoHS, UL, UKCA
Environmental	
Operating temperature	32° to 104°F (0° to +40°C)
Operating humidity	10% to 85%, Non-condensing
Storage temperature	14° to +158°F (-10° to +70°C)
Storage humidity	10% to 85%, Non-condensing
Power	
Powered by the CALICO main unit	

\* This item is not hot-swappable  
 \*\* Must be installed by a skilled professional