# **HDMI Cable**




This Ultra High Speed HDMI™ Cable has been verified by HDMI Authorized Testing Center. 48Gbps bandwidth for latest HDMI features, Dolby Vision, Dynamic HDR, Enhanced Audio Return Channel (eARC), Auto Low Latency Mode (ALLM), Variable Refresh Rate (VRR), Quick Media Switching (QMS), Quick Frame Transport (QFT). Supports HDCP2.3, 8K@120Hz/60Hz, 4K@144Hz/120Hz, and up to 10K resolution.

### PRODUCT OVERVIEW

This Ultra High Speed HDMI™ Cable has been verified by HDMI Authorized Testing Center. It can perfectly deliver 8K@120Hz/60Hz, 4K@144Hz/120Hz signal over 48Gbps bandwidth. The measured value of Intra-Pair Skew is far below the limit value (30ps). Superior construction combines 24K gold-plated connectors, foil & braid shielding for stable signal transmission. With the robust EMI shield, the cable is able to reduce the probability of interference with nearby wireless services. It is compatible with PS5, Xbox Series X, Nintendo Switch, Apple TV, and other HDMI-enabled devices to 8K TVs, 8K A/V receivers for an ultimate viewing experience. Backward with earlier versions of HDMI and can be used with existing HDMI devices.

### **DIAGRAM**



### **FEATURES**

- Certified Ultra High Speed HDMI™ Cable
- 8K@120Hz/60Hz, 4K@144Hz/120Hz resolution, 48Gbps bandwidth
- Dolby Atmos, TrueHD & DTS:X, HD Master Audio
- Foil & braided shielding
- 24K gold-plated HDMI connectors
- 3-Year Warranty

#### **SPECIFICATIONS**

HDMI Sig	nal Su	pport
----------	--------	-------

HDMI Standards	HDMI 2.1
Video Format	8K@120Hz/60Hz, 4K@144Hz/120Hz
Data Rate	48Gbps
Control Signal	HDCP 2.3/EDID/ CEC/ DDC
Connector	HDMI Type A Connector
Audio Support	Dolby Atmos, Dolby TrueHD, DTS:X, DTS-HD Master Audio
Physical Properties	
Op. Temp.	0°C to 50°C
Humidity	0% to 85% RH
Rending Radius	12mm

12kg

# **Comparison Chart**

**Pulling Force** 

	HDMI 2.1	HDMI 2.0	HDMI 1.4
	8K@60Hz	4K@60Hz	4K@60Hz
	Dynamic and Static HDR	Static HDR	Χ
<b>Image Quality</b>	Auto Low Latency Mode (ALLM)	Χ	Χ
	Variable Refresh Rate (VRR)	Χ	Χ
	Quick Media Switching (QMS)	Χ	Χ
	eARC	ARC	ARC
Sound Quality	32 Audio Channels	32 Audio Channels	8 Audio Channels
	48Gbps Bandwidth	18Gbps Bandwidth	10.2Gbps Bandwidth
Sending Rate	Quick Frame Transport (QFT)	Χ	Χ
	Display Stream Compression (DSC)	Χ	Χ

# **ORDERING INFORMATION**

Model No.	Product Description	
CBL-H600-010	1M, 30AWG	
CBL-H600-020	2M, 30AWG	
CBL-H600-030	3M, 30AWG	
CBL-H600-050	5M, 26AWG	

