

CH-U350TX

HDMI/VGA over IP Transmitter with USB/KVM Extension




This unit is part of a 4K UHD Multi-Function Extension system that allows you to extend HDMI or VGA signals along with KVM using the TCP/ IP protocol over regular Cat.5e/6/7 network cable. This extender supports the transmission of Ultra High-Definition signals (up to 4K@30Hz YUV 4:4:4 or 4K@60Hz YUV 4:2:0) with audio and USB up to 100m on a single cable. The transmission distance can be further extended (up to 100m per segment) by using gigabit network switches, allowing the user to cascade the system without signal loss or introducing delay. It is also possible to have the extension system's Transmitter operate in multicast mode, allowing you to send a single AV signal to a large number of Receivers within the same local network. It is useful for user to create large multi-display video walls with amazing simplicity.

PANELS



DIAGRAM



FEATURES

- Video, audio and control transmission over TCP/IP in Unicast (point-to-point) or Multicast (single-to-many) modes
- Support with 90° increments rotation
- The analog Line In on the Transmitter sends audio directly to the analog Line Out and is inserted into the HDMI output on connected Receivers
- The Mic In on the Receiver sends audio directly to the analog Line Out on the Transmitter
- Both Tx and Rx may powered directly by PoE when connected to a Gigabit Ethernet switch that provides PoE (802.3af)
- Supports USB keyboard, mouse and storage extension and IR, RS-232 bypass
- Unit can be controlled via WebGUI, Telnet, and front panel controls

SPECIFICATIONS

Interfaces

Input Port	1 HDMI (Type-A) 1 VGA 1 Unbalanced Stereo (3.5mm)
-------------------	---

Output Port	1 VGA 1 Cat.5e/6/7 (RJ45) 1 Unbalanced Stereo (3.5mm)
--------------------	---

Control I/O	1 USB Type-B 1 IR Extender [3.5mm] 1 IR Blaster [3.5mm] 1 RS232
--------------------	--

Video

HDMI Compliance	2.0 (DVI 1.0)
HDCP Compliance	2.2
Input Signal Types	4K@60 8-bit YUV 4:2:0
Output Signal Types	4K@60 8-bit YUV 4:2:0

Resolutions

Maximum Input	HDMI	4096×2160p@60
	VGA	1920×1200p@60RB
Maximum Output	VGA	1920×1200p@60RB
	Cat.5e/6/7	4096×2160p@60

Audio

Input Signal Types	HDMI, Unbalanced Stereo
Output Signal Types	Unbalanced Stereo
Digital Formats	HDMI 2CH LPCM, 8CH LPCM, Standard Bitstream

Power

Power Supply	5V/2.6A
Power Consumption	7.15W (Full load)

Enclosure

Chassis Material	Metal (Steel)
Chassis Color	Black
Dimensions (W×H×D)	231.5mm×25mm×108mm [Case Only] 231.5mm×25mm×120mm [All Inclusive]
Weight	660g

Field Firmware Update

WebGUI

ORDERING INFORMATION

Model No.	Product Description
CH-U350TX	HDMI/VGA over IP Transmitter with USB/KVM Extension
CDPS-CS7	IP Master Controller
CH-U331TX	HDMI/VGA over IP Transmitter with USB/KVM Extension
CH-U331RX	HDMI/VGA over IP Receiver with USB/KVM Extension
CH-331H-TX	HDMI over IP Transmitter
CH-331H-RX	HDMI over IP Receiver