

CHAT[®] 150 | CHATAttach[®] 150 USB Speakerphones



Group USB speakerphone, powered by ClearOne's market leading HDConference[™] audio, enhances your web conferencing, unified communications and video conferencing experience in your personal workspace, huddle rooms, small and medium-size conference rooms with crystal-clear audio for business class performance.

HDConference Audio

 Distributed Echo Cancellation[®] and noise cancellation along with full-duplex performance and automatic level controls guarantee your conference calls to be natural with unmatched audio clarity free of any distractions

Full-duplex Speakerphone Capabilities on PCs or Laptops

+ Connect the CHAT 150 or the CHATAttach 150 to laptops & PCs via USB for handsfree audio

Acoustic Intelligence

 First-mic priority intelligently activates only the microphone closest to the person speaking, preventing the amplification of ambient noise and room reflections

Expandable Design

 Daisy-chainable design can expand up to two complete speakerphones to cover medium or large rooms. Full speakerphone expandability allows both mic and speaker to cover the entire room along with flexibility of control using any speakerphone

Internet Telephony

VENUES

Conference Rooms/Boardrooms

VoIP Softphones



Web Conferencing



CHAT® 150 | CHATAttach® 150

Components/Room Applications





Part# 800-156-202

ection Cable

art# 830-156-200



Two CHAT 150 Units # 910-156-200





Cable



CHAT 150



CHATAttach 150



USB 2.0 Connection Cable Part# 830-156-200

CHATAttach Power Supply Part# 551-156-200 Part# 830-156-010L

CHATAttach Quick Start Guide Part# 800-156-225

PRODUCT SPECIFICATIONS

System Requirements:

- Microsoft Windows 7, 8, 10 (For any firmware upgrades, use Win7)
- Mac OS

Connections:

USB:

- Version 2.0 Compatible
- Type: Mini-B Female

Keyed Connector:

• Keyed RJ-45 (8-conductor)

Line Input/Output via VC Breakout Box (BOB):

Frequency Response:

- 20Hz 20 kHz +/- 1 dB
- Maximum Level: +6 dBu
- Input Impedance: 10 kΩ
- Output Impendance: 50 Ω

Controls:

- Volume Up
- Volume Down
- Microphone Mute

Audio:

Speaker:

- Bandwidth: 190 Hz 20 kHz
- Max Output Level: 85 dB SPL @ 1 foot (0.30 meter)
- Microphone:
- Bandwidth: 50 Hz 7.75 kHz

Environmental:

Operting Temperature:

• 41 - 104° F (5 - 40° C)

Processing:

- Full Duplex
- Distributed Echo Cancellation (D.E.C.)®
- · Noise Cancellation (NC)
- Automatic Level Control (ALC)
- · Line Echo Cancellation (LEC) Selectable
- First-Mic Priority

Power:

- USB: • 5 VDC @ 500 mA Maximum External:
- Input: 100 240 VAC
- Output: 9 VDC @ 560 mA
- Tip: Power
- · Ring: Ground

Mechanical:

- Dimensions (W x D x H):
- 7.4" x 7.4" x 1.8" (18.8 cm x 18.8 cm x 4.6 cm) Weight:
- 1.17 lbs (0.53 kg)

Compliance:

- RoHS
- REACH
- FCC Class A Part 15
- ICES-003
- CE Listed
- UL Listed

Model Numbers:

910-156-200 CHAT 150 USB:

- Single CHAT 150 and Connecting Cable
- 910-156-200-00 CHATAttach 150:
- Two (2) CHAT 150 Devices, Connecting Cables and Power Supply

910-156-222 CHAT 150 Avaya:

 CHAT 150 and Connecting Cable to Avava Enterprise Phone

910-156-220 CHAT 150 Cisco:

- CHAT 150 and Connecting Cable to Cisco **Enterprise Phone**
- 910-156-230 CHAT 150 VC:
- CHAT 150 and Cable to Video Conference System

Accessory Part Numbers:

860-156-230L CHAT 150 VC Accessory Kit:

 Includes Video Conferencing Breakout Box, Power Adapter, International Power Clips, RCA Connection Cable, 25' Link Cable

860-156-222L CHAT 150 Avaya Accessory Kit:

• Includes Breakout Box for 2410, 2420, 4610 and 4621 Telephone Handsets, Power Adpater, International Power Clips, RJ-9/RJ-9 Telephone Cable, 25' Link Cable

860-156-220L CHAT 150 Cisco Accessory Kit:

- Includes Breakout Box for 7940, 7960, and 7970 Telephones, Power Adapter, International Power Clips, RJ-9/RJ-9 Telephone Cable, 25' Link Cable
- 910-156-225 CHATAttach Expansion Kit:

Tel: +1.800.945.7730

global@clearone.com

· Includes Cables, Power Supply and Quick Start Guide to Update Two (2) CHAT 150 Devices to CHATAttach

Tel: +1.800.945.7730

global@clearone.com

SALES AND INQUIRIES

Tel: +1 801.975.7200 TollFree: +1 800.945.7730 TechSales: +1 800.705.2103 Fax: +1 801.303.5711 sales@clearone.com

Tel: +1.800.945.7730 global@clearone.com

Tel: +1.800.945.7730 global@clearone.com

Other product names may be registered trademarks of their respective owners who do not necessarily en-dorse ClearOne or ClearOne's products. All rights reserved. Information in this document subject to change without notice. © 2016 ClearOne. DOC-802-156-003. Revisison 2.0 2016