VIDEO COLLABORATION


COLLABORATE® Live 300



COLLABORATE® Live solutions are the most versatile video collaboration room systems of their kind in the market.

COLLABORATE Live 300 is a complete video collaboration system ideal for small meeting rooms, with everything needed in a single solution for professional audio and video collaboration.

- > One CHAT 150 speakerphone provides crystal-clear audio.
- One UNITE® 150 PTZ HD camera with 1080p30, 12x optical zoom to capture all participants in the room.
- > User interface as intuitive and simple as familiar mobile or tablet devices.
- > Monitor, control, and audit Versa Pro CT with CONVERGENCE™ unified AV network management software
- > COLLABORATE Space is a powerful collaboration application with a full suite of audio, video, and meeting tools in a persistent space.



Pro-quality speakerphone audio
The CHAT® 150 speakerphone provides
crystal-clear audio.



Easy to Use

User interface is as intuitive and simple as that of familiar tablets and mobile devices.

APPLICATIONS

- Video conferencing
- Audio conferencing
- Cloud video collaboration
- Wireless presentation
- Whiteboard

WORKSPACES

- Small meeting rooms
- Executive offices



VIDEO COLLABORATION

VISUAL COLLABORATION

COLLABORATE® Live 300

COLLABORATE LIVE 300

- •COLLABORATE Live 300 codec appliance
- •UNITE 150 PTZ HD camera
- CHAT 150 speakerphone
- Power supplies, cables and accessories
- COLLABORATE Space application (90 days)
- One-year support and maintenance with warranty

COLLABORATE LIVE 300 CODEC APPLIANCE

- Video input: 1x USB 3.0
- Video output: 1x HDMI, 1x Display port
- Audio input: USB (Digital audio)
- · Audio output: USB, S/PDIF
- •USB: 4x USB 3.0

UNITE 150 PTZ HD CAMERA

- •Full HD 1080p30
- •73° wide-angle view
- •USB 3.0/2.0, Line In
- •Remote control, USB (UVC), RS-232
- •±170° pan, -30° to +90° tilt, 12x optical zoom

CHAT 150 SPEAKERPHONE

- ClearOne HDConference™ audio processing
- •Three built-in microphone array with 360° pickup
- Large loudspeaker with Max Output Level: 85 dB SPL
 @ 1 meter
- · Wideband audio frequency response (20Hz-20kHz)

VIDEO CHARACTERISTICS

- •Resolution up to 1080p @ 30 fps (Rx)
- •H.261, H.263, H.263+/++
- •H.264/AVC High Profile up to 6Mbps
- •H.264/SVC (Skype for Business)

- 20KHz: AAC-LD
- 14KHz: G.722.1 Annex C
- 7KHz: G.722, G.722.1
- 3.4KHz: G.711, G.723.1, G.728. G.729. AMR (3G)

DATA CHARACTERISTICS

- •H.239 support for data sharing
- •Resolution up to 1080p
- Data inputs via wireless, datapoint (HDMI-to-USB adapter)

CONTROL

- Web-based management and control
- Telnet API for 3rd party control
- AMX and Crestron modules

PART NUMBER

•930-3001-302

AUDIO STANDARDS

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way Suite 500

Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200 Fax: 801.303.5711 International

Tel: +1.801.975.7200 global@clearone.com Sales

Tel: 801.975.7200 sales@clearone.com

Tech Support

Tel: 801.974.3760

tech.support@clearone.com