CPLUS-SDI2H




The SDI to HDMI Converter allows SD, HD, 3G and 12G-SDI signals to be shown on HDMI display. This means that it is now easier for professionals to distribute and extend their SDI signal while giving the ability to display work on HDMI displays. Furthermore, thanks to L/R audio outputs users can output audio in analog formats while the loop-through 12G-SDI design benefits users by letting them simultaneously show content on both SDI and HDMI displays.

PANELS



DIAGRAM



12G-SDI to HDMI Converter

FEATURES

- Supports SDI output distance up to 60 meters (12G-SDI), 80 meters (6G-SDI) 100 meters (3G-SDI), 200 meters (HD-SDI), or 300 meters (SD-SDI) Note:
 - 1. Tested with Belden 1694A Cable. Operating distances may vary if used with cables of different specifications.
 - This product does not process HDCP encrypted input signals. There will be no video output when the input signal contains content that is HDCP encrypted.
- Integrated audio embedded up to 8 CH PCM 48 kHz for HDMI or 2 CH (external L/R) for DVI audio
- Support SDI signal re-timing Cable Driver

SPECIFICATIONS

Interfaces			
Input Port	1 12G-SDI (BNC)		
Output Port	1 12G-SDI(BNC) 2 HDMI(Type-A) 1 Unbalanced Stereo (3.5mm)		
Video			
HDMI Compliance	HDMI 2.0 (DVI 1.0)		
HDCP Compliance	Not Supported		
Input Signal Types	4K@60 8bit 4:4:4		
Output Signal Types	4K@60 8bit 4:4:4		
	Resolutions		
Maximum Input	SDI	4096×2160p@60 (YUV 4:2:2)	
Maximum Output	HDMI	4096×2160p@60 (YUV 4:2:2)	
	SDI	4096×2160p@60 (YUV 4:2:2)	
Power			
Power Supply	5V/2.6A DC (Locking)		
Power Consumption	4.95W (Full Load)		
Enclosure			
Chassis Material	Metal (Steel)		
Chassis Color	Black		
Dimensions (W×H×D)	128mm×25mm×75mm [Case Only] 128mm×25mm×94mm [All Inclusive]		
Weight	347g		
Field Firmware Update			
USB			

ORDERING INFORMATION

Model No.	Product Description
CPLUS-SDI2H	12G-SDI to HDMI Converter
CPLUS-H2SDI	HDMI to 12G-SDI Converter
CPLUS-SDI2H-W	12G-SDI to HDMI Converter
CPLUS-H2SDI-W	HDMI to 12G-SDI Converter