

CRS-AOCH/CLR/60

Rental & Staging Active Optical 4K High-Speed HDMI Cable

| HDMI | 4K/60 UHD (4:2:0) | 4K/60 UHD (4:4:4)



CRS-AOCH/CLR/60 is an active optical HDMI cable for 4K@60Hz (4:4:4) resolutions over distances up to 100m (328ft). Built with a TPU-rated (thermoplastic polyurethane) jacket that has excellent abrasion resistance, tensile strength and high tear resistance, this cable can withstand the most demanding conditions in rental, staging and production setups. And it is thinner, lighter and more flexible than copper cables.

CRS-AOCH/CLR/60 includes transparent EDID, HDCP, and HBR support and reduced risk of EMI and RFI interference for critical AV installations. The cable's HDMI ends are color coded (green for source and red for display) to prevent installation errors

FEATURES

Max. Resolution - 4K@60Hz (4:4:4), 8-bit, full HD, 3D Deep Color across all lengths

Max. Data Rate - 18Gbps

Embedded Audio - PCM 8-channel, Dolby Digital True HD and DTS-HD Master Audio

HDMI Support - HDCP 2.2, HDR, EDID and CEC

High-Quality Connectors - 24K gold-plated, corrosion-resistant and best possible connectivity

EMI & RFI Immunity

No External Power - Active units are powered via the HDMI connector

Thin Construction - 4.5mm (0.18") diameter

Jacket Construction - TPU (Thermoplastic Polyurethane)

RoHS 2011/65/EU Compliant

Varied Selection of Lengths - Available in versions from 10m to 100m (33 to 328ft)



TECHNICAL SPECIFICATIONS

Inputs HDMI: On a Male HDMI type-A 24K gold plated connector with green case

Outputs HDMI: On a Male HDMI type-A 24K gold plated connector with red case

OVERALL General: Hybrid Optical Fiber Cable

Fiber Optic: Multi-mode Fiber

Conductors: 6x28AWG (7/0.127mm)

MECHANICAL Bending Radius: 90mm

Connector Max. Pulling Strength: 22lbs/10kg

Max. Compression Load Resistance: 500N (50kg, 110lbs)

JACKET Material: C TPU (Thermoplastic Polyurethane)

Color: Black

Diameter: 4.5mm

Video Max. Resolution: 4K@60Hz 4:4:4 across all lengths

Max. Data Rate: 18 Gbps

Supported Color Spaces: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601

Embedded Audio: Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio™,

DVD Audio, SA-CD

HDMI Support: HDCP 2.2, HDR, EDID and CEC

Power No external power supply is needed (draws current from the source). If source

power is not sufficient, connect the AD-HM/HF/UAM - USB to HDMI power injector

to an external power supply

Consumption: 0.65W max

STANDARDS COMPLIANCE RoHS: 2011/65/ EU





CONFIGURATIONS

| CRS-AOCH/CLR/60- 33 | Rental & Staging Active Optical High-Speed HDMI Cable |
|-------------------------|---|
| CRS-AOCH/CLR/60- 50 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 66 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 98 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 131 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 164 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 197 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 230 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 262 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 295 | Rental & Staging Active Optical High-Speed HDMI Cable |
| CRS-AOCH/CLR/60- 328 | Rental & Staging Active Optical High-Speed HDMI Cable |
| | |