Ceiling Speaker

AUDAC

Features

- Installation ceiling loudspeaker
- Very attractive design
- Double cone loudspeaker
- Very powerfull magnet
- Detachable aluminium grill
- 3 different power tappings
- Beautifull warm sound reproduction
- Quick and simple mounting

Applications

- Public buildings
- Business offices
- Warehouses
- Shops
- Hotels
- Restaurants



The CS series loudspeakers are AUDAC's ceiling speakers, designed for use any possible application.

Wherever sound is needed without obvious speakers, or in larger buildings where the sound has to be spread over an enormous space, the CS Series speakers will offer the best solution.

The use of high quality components, combined with the application of a standard 100V line transformer, makes the CS series a range of speakers that can be used in any situation. Even if it's a standard low impedance Hi-Fi installation or a larger 100V PA system.

The CS65 contains a double cone loudspeaker with a diameter of 120 mm and a very powerful magnet that will ensure a beautiful warm sound reproduction for music and speech.

The power can be set in 3 adjustable steps of impedance for 100V and 1 step for 8 Ohm standard low impedance applications.

- 6 Watt, 3 Watt, 1.5 Watt @ 100V
- 10 Watt @ 8 Ohm

Below the detachable grill, there are four screws for a quick and simple attachment of the unit.

The removable grill and housing of the speaker can be painted, to blend in with the structure the speaker is built in. With these speakers comes an easy cut-out template to accomplish easy installation.

A 16 Ohm version is also available: CS65/D.

▶ Specifications

SYSTEM SPECIFICATIONS Max. power	40 W	
<u> </u>	1 7 11	
RMS power	20 W	
Power line transformer 1	6 W / 1600 Ohm	
Power line transformer 2	3 W / 3300 Ohm	
Power line transformer 3	1.5 W / 6600 Ohm	
Frequency response -3dB	70 Hz - 14 kHz	CS65
	60 Hz - 18 KHz	CS65/D
Sound pressure W/1m	93 dB	
Sound pressure max W / 1m	106 dB	
Impedance	8 Ohm	CS65
	16 Ohm	CS65/D
PRODUCT FEATURES		
Dimensions (WidthxHeightxDiameter)	205 x 205 x 70 mm	
Weight net	1.34 Kg	CS65
	1.16 Kg	CS65/D
Drivers	120 mm	
Construction	ABS housing	
Cut-out measurement	Ø 167 mm	
Mounting	4 Screws clamps	
Front finish	White aluminium grill	
Colour	White (RAL 9010)	
SHIPPING & ORDERING	,	
Packaging	Carton box	
Shipping weight & volume	1.43 Kg - 0.0053 Cbm	CS65
	1.25 Kg - 0.0053 Cbm	CS65/D
Accessories	Foam inlay White	
	Cut-out template	

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products