

# CS74

## Ceiling Speaker

# AUDAC

### ► Features

- High-quality 2-way ceiling loudspeaker
- Very attractive design
- Detachable aluminium grill
- 3 different power tapings
- True-to-nature sound reproduction
- Quick and simple mounting
- Very wide frequency response
- Easy to hide away

### ► Applications

- Public buildings
- Business offices
- Warehouses
- Shops
- Hotels
- Restaurants



The CS series loudspeakers are AUDAC's ceiling speakers, designed to be used in any possible application.

Wherever sound is needed without obvious speakers, or in larger buildings where the sound has to be spread over an enormous space, the CS Series speakers will offer the best solution.

The use of high quality components, combined with the application of a standard 100V line transformer, makes the CS series a range of speakers that can be used in any situation. Even if it's a standard low impedance Hi-Fi installation or a larger 100V PA system.

The CS74 is an extremely high-quality ceiling loudspeaker for installation purposes. It is a 2-way loudspeaker, with a diameter of 5 1/4" mm for the low frequencies, and a tweeter, mounted in the center, for the high frequencies. This ensures a brilliant reproduction of all kinds of music.

Because of the moisture-proof treatment and the aluminium grill, the loudspeaker can be placed outdoor or in damp rooms.

Below the detachable grill, there are four screws for a quick and simple attachment of the unit.

The removable grill and housing of the speaker can be painted, to blend in with the structure the speaker is built in. With these speakers comes an easy cut-out template to accomplish easy installation.

Available in White (/W) and Black (/B)

### ► Specifications

SYSTEM SPECIFICATIONS		
Max. power	60 W	
RMS power	30 W	
Line Transformer Power Tap 1	6 W / 1667 Ohm	
Line Transformer Power Tap 2	3 W / 3333 Ohm	
Line Transformer Power Tap 3	1.5 W / 6667 Ohm	
Frequency response -3dB	Fo Hz - 20 kHz	
Sensitivity 1W/1m	90 dB	
Sound pressure max W / 1m (8 Ohm)	104 dB	
Sound pressure max W / 1m (100 V)	98 dB	
Impedance	8 Ohm	
Crossover	Passive built-in	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	Ø 205 x 90 mm	
Weight net	1.5 Kg	
Drivers (Coaxial)	HF	1"
	LF	5 1/4"
Construction	ABS housing	
Mounting	4 Screws clamps	
Cut-out measurement	Ø 167 mm	
Built-in depth	100 mm	
Front finish	White aluminium grill	
Colour	White (RAL 9010) - CS74/W	
	Black (RAL 9005) - CS74/B	
SHIPPING & ORDERING		
Packaging	Carton box	
Shipping weight & volume	1.58 Kg - 0.0055 Cbm	
Accessories	Foam inlay	
	Cut-out template	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		