CSA506

Ceiling Speaker


AUDAC

Features

- Two power taps
- Minimal installation depth
- Light weight design
- Quick mounting clamps



- Public buildings
- Business offices
- Warehouses
- Shops
- Hotels
- Restaurants



It ensures a good reproduction of speech and background music. It is fitted with a 100V line transformer with power taps for 6W and 3W to be used in large 100V PA systems.

The speaker is constructed in a way that the framework is also used as base construction for the speaker cone.

It has Quick mounting clamps, whereby the speakers built-in depth is reduced to only 6 cm, and the weight is reduced to 500g.



▶ Specifications

SYSTEM SPECIFICATIONS	
Max. power	10 W
RMS power	6 W
Line voltage	100 V
Power taps	6 W / 1666 Ohm
	3 W / 3333 Ohm
Frequency response -3dB	100 Hz - 15 kHz
Sound pressure W/1m	93 ± 3 dB
PRODUCT FEATURES	
Dimensions (Diameter x Depth)	Ø 175 x 60 mm
Cut-out measurement	Ø 150 mm
Weight net	0.5 Kg
Drivers	5"
Construction	ABS
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products