


In Celebration of Our New

Special Promotion



→ Now your people can look as sharp as they are!

COLLABORATE All-In-One combines an HD Video Software codec with ClearOne's professional audio



Now includes

HD Video Conferencing

Solution Bundle

HD Video	Standards-based (SIP/H.323) 1280x720 - 30fps
HD Audio	ClearOne Professional Audio Mixer Daisy chainable Microphone array
HD Display	1920x1080 46" HD LCD
Control Options	Remote Control, Wireless Keyboard and mouse, Optional tabletop dialer
Mounting Options	Wall Mount, Table stand, Optional Multimedia Cart

Video Conferencing	HD Video Conferencing Multipoint option through MCU Interoperable with SIP/H.323 endpoints
Data Collaboration	Data sharing (H.239) Recording and Streaming
Unified Communication	Google Talk, IBM Sametime, Microsoft Lync, Skype and others
Perfect for	Conference and meeting rooms, Executive offices



Advanced data sharing capabilities with no PC required - presentations or videos, open various file types from USB storage devices.

System Includes

- | | | |
|--|-------------------------------------|-------------------------------|
| + 46" 1080p LCD display | + Built-in Professional audio mixer | + Remote control |
| + Built-in HD Video conferencing codec | + HD Microphone array | + Wireless keyboard and mouse |
| + Recording and streaming license | + HD Soundbar | + Wall mount or Foot stand |
| + 720p USB camera | | |

Functional Specifications

VIDEO CHARACTERISTIC

Video Specifications

Transmission speed (H.323 / SIP):
64Kbps – 6MBps
ISDN: 64Kbps – 512Kbps (4 x BRI) (*)

Video Standards

H.261, H.263, H.263+/+ +, H.264,
H.264 - UP TO 6Mbps

Live Video Resolution

720p60 (1280 x 720 pixels),
16:9 VGA (672 x 348 pixels),
4CIF (704 x 576 Pixels), 4SIF (704 x 480 pixels),
VGA (640 x 480 Pixels), CIF (352 x 288 Pixels),
SIF (352 x 240 Pixels), QVGA (320 x 240 Pixels)
Up to 1080p60 RX, (1920 x 1080 pixels)

Video Frame Rate

Up to 30 fps

Camera

HD USB, (Logitech C910)
Auto focus, 1080p/30fps

AUDIO CHARACTERISTICS

INTERACT Microphone

Ships with One Mic (Two Mic Limit - see
Accessory Part Numbers for Additional Mic PN)

Coverage: 360°

Connection:

Daisy-chain RJ-45 with CAT5 Cable

Max Monitor-Pod Distance: 75'

Microphone Sensitivity: -45 dBu

COLLABORATE Soundbar

Audio Operation:

100 Hz - 20 kHz

Channels: Mono

Sensitivity:

85 dB 1W @ 1 foot (0.3 meter)

Power: 20W per Channel

Impedance: 4 Ω

INTERACT Audio Mixer

Frequency Response:

20 Hz - 15 kHz +/- 1dB

Dynamic Range:

>80 dB (Non-A Weighted)

THD+N < 0.02%

Processing:

AEC, NC, AGC, Gating, NOM

Line Inputs:

Two (2) Unbalanced RCA

Line Outputs:

Two (2) Unbalanced RCA

Amplifier Outputs:

Four Ω Stable (5W into 4 Ω)
Connection: Binding Post Terminals

DATA CHARACTERISTICS

Data Specifications

Data sharing methods Laptop plug in
(via Tabletop Pod) USB Storage key
Documents: PPT, PPTX, PPS, m PPSX, DOC,
DOCX,XLS, XLSX Video clips (AVI, MPEG, WMV,
etc) Audio clips (WAV, MP3), Graphic files (BMP,
GIF, TIF etc) H.239 support, Tandberg DuoVideo
support, Sending & receiving capability
1 live video source + 1 data source

Resolutions Supported

XGA, SVGA, 4CIF, VGA, CIF

TELEPHONE INTERFACE

Telephone Audio Performance

Conditions: Unless otherwise specified, all
measurements are performed with Transmit
Limiter and Receive ALC disabled

Frequency Response:

250 Hz to 3.3 kHz ±1 dB THD+N: < 0.30%
re-max level 250 Hz to 3.3 kHz
SNR: > 62 dB re-max level

Telco Line Echo Cancellation

Tail Time: 32 ms
Null: 55 dB Nominal

Telephone Noise Cancellation

Noise Cancellation 6-15 dB Attenuation

NETWORK CHARACTERISTICS

H.323 QoS Features

DiffServ, IP Precedence, Firewall Port Sync,
Port pinholing NAT IP address mask, Adaptive
Bandwidth Adjustment, Packet loss recovery (FEC),
Packet duplication control
Packet ordering, Jitter correction,
Overhead prediction Lip sync correction,
Max packet size adjustment

Dialing Modes

Manual, Speed dial, Personal address book,
Online directory, Multicast chair, Broadcast
viewer,
Telnet API for AMX/Cretron

Security & Encryption

Encryption using H.235 (AES)
Supports Collaborate NetPoint (Firewall Traversal)
Network address translation
Supports restricted access to users via admin

Control

International remote control
Embedded web-based management
Telnet API for AMX/crestron

Directory Services

1000+ local number directory
10,000+ global number directory
H.350 support (MXM Mode)
LDAP online directory support,
OpenLDAP
Microsoft ILS
SiteServer
Active Search and Filter queries

FULL HD (1080p) DISPLAY

46" LCD, 1080p resolution,
Built-in quad core processor
Windows 7 OS
4Gb Ram (built in)
Internal Storage (500Gb)
Built-in HDConference® Audio mixer

PHYSICAL CHARACTERISTICS

Approximate Dimensions

W: 44.5" (1130.3 mm)

H: 32.0" (812.8 mm)

D: 5.0" (127.0 mm)

46" Display Weight: ≈95 lbs. (43 kg)

VESA Mounting Holes

M6 1 mm thread pitch

100 mm & 200mm Vertical

600 mm Horizontal

ENVIRONMENTAL

Operating Temperature:

32 - 95° F (0 - 35° C)

Operating Time per 24-hour Period:

12 Hours Powered Max

Humidity: 15 - 80%

Compliance

EMC: FCC Part 15 Class A

EMI: EN55024:1998+A1 & A2

EN55022:2006

IEC61000-4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11, 3-2, 3-3

Safety:

UL60950-1:2006+A11:2009

PART NUMBERS

930-401-100 COLLABORATE Console,
Single display with Windows OS

ClearOne Contacts

HEADQUARTERS:

Salt Lake City, UT USA

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

Tel: 801 975 7200

Toll Free: 800 945 7730

Fax: 801 977 0087

E-mail: sales@clearone.com

EMEA

Tel: 44 1454 616 977

E-mail: global@clearone.com

APAC

Tel: 801 303 3388

E-mail: global@clearone.com

LATAM

Tel: 801 974 3621

E-mail: global@clearone.com

TechSales

Tel: 800 705 2103

E-mail: techsales@clearone.com

Technical Support

Tel: 800 283 5936

E-mail: tech.support@clearone.com