

D 7313-H

High Speed Dome Camera Controller



- Joystick control of PTZ functions
- Preset position and pattern control
- Friendly user interface through LCD display
- Built in firmware upgrade circuits allows user to upgrade the firmware through RS-232 port easily
- Rubber keypad is easier to input commands
- Remote control via RS-485 interface
- Dome cameras, Multiplexers, P/T/Z receivers and All in one cameras can be controlled through this keyboard
- Maximum **255** devices can be controlled. (223 Dome Cameras or Receivers, 16 System Keyboards, 16 Multiplexers and one video Matrix.)

TECHNICAL SPECIFICATIONS

Dome Control		Manual Pan/Tilt/Zoom
		Preset
		Sequence
		Cruise
		Auto-Pan
		Zoom: Tele/Wide
Camera Lens Control	Focus	Near/Far/Auto
	Brightness	+/-
DVR/Multiplexer	Mode Selection	split screen mode: full, 2x2, 3x3, 4x4
	Menu Control	Yes
Supported Protocols		PELCO D&P, DSCP (Baud rate selectable)

GENERAL

Environment	Indoor
Controller Interface	RS-485
Operating Temperature	0° ~ 40 °C
Power Source	DC 12V
Power Consumption	5W
Dimensions	103mm (H) ×330mm (W) ×175mm (D)
Weight	1.7 kg

*The appearance and specifications of all items are subject to change without notice