

DHI-LDH43-WAI200L

Dahua 43 inch LCD Digital Signage



Series Overview

Simple and elegant, the LCD Digital Signage is built of metal and has an industrial-grade design. With its A-level LCD panel, it has a long lifespan and displays high quality visuals. It can access the network, support audio and videos, release multimedia information, and broadcast advertisements.

Functions

Rich Media

A wide variety of media can be inserted into your projects such as images, videos, audio and files in Word, Excel, PPT, TXT or PDF format. It also supports insertion of webpages, streaming media, scrolling subtitles, notifications and more.

Program Plug-ins

Multiple elements can be incorporated into your projects, such as the weather, time and countdown timer, to suit your needs.

Local Release

Media can be conveniently imported to the digital signage through a USB flash drive to create and release projects.

Release through the Network

Projects can be easily created on the Media Publishing System (MPS) platform when the device is connected to the network, and then directly sent to the terminal device to be played.

Play Plans

The system simplifies broadcasting with general and cut-in plans. General plans, once activated, control how media is played on terminal devices. Cut-in plans can be directly released without approval.

- Designed with an industrial-grade panel. It works up to 24 hours a day.
- Includes a mainstream quad-core CPU and Android system.
- Plays and releases programs in multiple modes.
- With intelligent split screen, its page layout can be freely adjusted, making it suitable for a variety of scenes.
- Designed with B/S architecture, the device manages programs by time and location, and generates operation reports.
- Supports encrypting platform data transmission, multi-level permission review for program release and terminal password protection.
- The device offers unified platform management, and can be remotely controlled by the platform.

Play Modes

The two play modes, carousel and temporary plan, add variety to the presentation of your projects. Carousel mode plays multiple media in a loop, with no need for manual configuration. Temporary plan mode fills in to play your media when there are no general plans and cut-in plans. It can be played with scrolling subtitles.

Custom Play Time

The play schedules are highly flexible. General plans can be scheduled to play weekly or you can personalize your own time schedule for them. Cut-in plans can be tailored by period, duration, and the number of play times.

Scrolling Subtitles

Subtitles can be set to scroll smoothly across the screen, displaying your desired content.

Split Screen

The screen can be divided into multiple windows, with each one showcasing different content.

Remote Management

From the comfort of the platform, you can remotely power on and off the device, restart it, turn its display on and off, rotate its screen, and adjust its brightness and volume.

Scene

Ideal for communities, malls, supermarkets, hotels, enterprises, the government and various industries such as the advertising, catering, entertainment, tourism, culture, sports, education, finance, and healthcare industries.

WAI Series | DHI-LDH43-WAI200L

Technical Specification		General			
LCD Panel		Power Supply	180-264V, 50/6	50Hz	
Panel Dimensions	43 inch	Power Consumption	≤270 W	≤270 W	
Backlight	DLED	Standby Power Consumption	≤15 W with far	\leq 15 W with fans	
LCD Technology	IPS	Operating Temperature	0 °C to +40 °C (0 °C to +40 °C (+32 °F to +104 °F)	
Aspect Ratio	9: 16	Storage Temperature	-10 °C to +60 °	-10 °C to +60 °C (14 °F to +140 °F)	
Brightness	3000 cd/m ² (typ.)	Operating Humidity	10%-85% (RH)	10%–85% (RH), non-condensing	
Contrast	1200: 1 (typ.)	Storage Humidity	10%–90% (RH)	10%–90% (RH)	
Display Colors	8 bit, 16.7M colors	Product Material	Metal casing	Metal casing	
Resolution	1080 (H) × 1920 (V)	Casing Color (Frame/Re	ar) Black	Black	
Viewing Angle	178° (H); 178° (V)	Product Dimensions	568 mm x 980	568 mm x 980 mm x 85.3 mm	
Response Time	8 ms (typ.)	Product Dimensions	308 11111 X 380	505 mill x 505 mill x 65.5 mill	
Surface Treatment	Haze 25%	Packaging Dimensions	Packaging Dimensions 1130 mm x 236		
Built-in System		Net Weight	32kg	32kg	
Operating System	Android 11.0	Gross Weight	40kg	40kg	
CPU	4 cores A55, 1.92 GHZ	Installation	Ceiling mount (Wall mount/flo	(default) oor stand (extra bracket required)	
RAM	4 GB	Display Mode		Portrait (default), landscape	
ROM	32 GB		all Mount VESA 400 mm × 300mm		
Video Decoding	H.265 HEVC MP-10@L5.1 up to 2160p@60 fps H.264 AVC HP@L5.1 up to 2160p@30 fps VP9 Profile 2 up to 2160p@60 fps H.264 MVC up to 1080p@60 fps MPEG-4 ASP@L5 up to 1080p@60 fps (ISO-13818)	Accessory	Accessory Ceiling mount bracket, power cord, legal and regulatory information, remote control, screw		
5	WMV/VC-1 SP/MP/AP up to 1080p@60 fps	Certification	Certification		
Function		Certifications	CE		
Audio Compression	MPEG-3, WMA, WAV	Ordering Informa	Ordering Information		
Video Compression	MPEG-4, H.264 AVC/MVC, H.265 HEVC	Туре	Model	Description	
Video Format	mp4, avi, mov, mkv, wmv			Dahua 43 inch LCD Digital	
Device Ports		LCD Digital Signage	DHI-LDH43-WAI200L	Signage	
Network Port	$1 \times RJ-45$ 10/100/1000 Mbps self-adaptive Ethernet port				
Wi-Fi	Optional (External Wi-Fi module)	Dimensions (mm	Dimensions (mm[inch])		
Bluetooth	NO	635			
Data Transmission Ports	1 × USB 2.0 ports (type A) 1 × USB 3.0 ports (type A) 1 × TF card slot, up to 128 GB	(ua)			
Video Input	1 × HDMI 2.1 (1080P @60Hz)				
Video Output	NO				
Audio Port	1 × 3.5 mm jack output	1912			
IR Receiver	Yes	R ý		• • • • • • • • • • • • • • • • • • •	
Speaker					
Built-in Speaker	2 × 5 W				

© 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product. Rev 002.000