

# DHI-LDH55-EAO400L

Dahua 55 inch Wall-mounted LCD Digital Signage



## Series Overview

Simple and elegant, the LCD Digital Signage is built of metal and has an industrial-grade design. With its A-level LCD panel, it has a long lifespan and displays high quality visuals. It can access the network, support audio and videos, release multimedia information, and broadcast advertisements.

## Functions

### Rich Media

A wide variety of media can be inserted into your projects such as images, videos, audio and files in Word, Excel, PPT, TXT or PDF format. It also supports insertion of webpages, streaming media, scrolling subtitles, notifications and more.

### Program Plug-ins

Multiple elements can be incorporated into your projects, such as the weather, time and countdown timer, to suit your needs.

### Local Release

Media can be conveniently imported to the digital signage through a USB flash drive to create and release projects.

### Release through the Network

Projects can be easily created on the Media Publishing System (MPS) platform when the device is connected to the network, and then directly sent to the terminal device to be played.

### Play Plans

The system simplifies broadcasting with general and cut-in plans. General plans, once activated, control how media is played on terminal devices. Cut-in plans can be directly released without approval.

- Designed with an industrial-grade panel. It works up to 24 hours a day.
- Includes a mainstream quad-core CPU, Android system, and decodes up to 4K resolution.
- Plays and releases programs in multiple modes.
- With intelligent split screen, its page layout can be freely adjusted, making it suitable for a variety of scenes.
- Designed with B/S architecture, the device manages programs by time and location, and generates operation reports.
- Supports encrypting platform data transmission, multi-level permission review for program release and terminal password protection.
- The device offers unified platform management, and can be remotely controlled by the platform.

## Precautions

**To ensure the normal operation of outdoor devices, please confirm application scenarios with our sales engineers. Additionally, the filter needs to be cleaned every three months and replaced once a year.**

## Play Modes

The two play modes, carousel and temporary plan, add variety to the presentation of your projects. Carousel mode plays multiple media in a loop, with no need for manual configuration. Temporary plan mode fills in to play your media when there are no general plans and cut-in plans. It can be played with scrolling subtitles.

## Custom Play Time

The play schedules are highly flexible. General plans can be scheduled to play weekly or you can personalize your own time schedule for them. Cut-in can be tailored by period, duration, and the number of play times.

## Scrolling Subtitles

Subtitles can be set to scroll smoothly across the screen, displaying your desired content.

## Split Screen

The screen can be divided into multiple windows, with each one showcasing different content.

## Remote Management

From the comfort of the platform, you can remotely power on and off the device, restart it, turn its display on and off, rotate its screen, and adjust its brightness and volume.

## Scene

Ideal for communities, malls, supermarkets, hotels, enterprises, the government and various industries such as the advertising, catering, entertainment, tourism, culture, sports, education, finance, and healthcare industries.

**Technical Specification**

**LCD Panel**

Panel Dimensions	55 inch
Backlight	DLED
LCD Technology	IPS
Aspect Ratio	16: 9
Brightness	2500 cd/m <sup>2</sup> (typ.)
Contrast	1200: 1 (typ.)
Display Colors	10 bit (8 bit + FRC), 1.07B colors
Resolution	3840 (H) × 2160 (V)
Viewing Angle	178° (H); 178° (V)
Response Time	8 ms (typ.)
Reflective	<3%

**Built-in System**

Operating System	Android 11.0
CPU	4 cores A55, 1.92 GHZ
RAM	4 GB
ROM	32 GB
Video Decoding	H.265 HEVC MP-10@L5.1 up to 2160p@60 fps H.264 AVC HP@L5.1 up to 2160p@30 fps VP9 Profile 2 up to 2160p@60 fps H.264 MVC up to 1080p@60 fps MPEG-4 ASP@L5 up to 1080p@60 fps (ISO-13818) WMV/VC-1 SP/MP/AP up to 1080p@60 fps

**Function**

Audio Compression	MPEG-3, WMA, WAV
Video Compression	MPEG-4, H.264 AVC/MVC, H.265 HEVC
Video Format	mp4, avi, mov, mkv, wmv

**Device Ports**

Network Port	1 × RJ-45 10/100/1000 Mbps self-adaptive Ethernet port
Wi-Fi	No (Can be customized)
Bluetooth	NO
Data Transmission Ports	1 × USB 2.0 ports (type A) 1 × USB 3.0 ports (type A) 1 × TF card slot, up to 128 GB
Video Input	1 × HDMI 2.1 (4K @60Hz)
Video Output	NO
Audio Port	1 × 3.5 mm jack output
IR Receiver	Yes

**Speaker**

Built-in Speaker	2 × 5 W
------------------	---------

**General**

Power Supply	220 VAC, 50/60 Hz
Power Consumption	≤450 W
Operating Temperature	-20 °C to +45 °C (-4 °F to +113 °F)
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Operatng Humidity	5%–90% (RH), non-condensing
Storage Humidity	5%–90% (RH), non-condensing
Protection Level	IP55
Cooling Method	Fan-cooling
Product Material	Metal casing
Casing Color (Frame/Rear)	Black
Product Dimensions	1450 × 920 × 150mm (without wall mount bracket)
Packaging Dimensions	1620 × 1190 × 400mm
Net Weight	118kg(260.1lb)
Gross Weight	136kg(299.8lb)
Installation	Wall mount
Display Mode	Landscape only
Accessory	Wall-mount bracket, user's manual, legal and regulatory information

**Certification**

Certifications	CE, ERP
----------------	---------

**Ordering Information**

Type	Model	Description
LCD Digital Signage	DHI-LDH55-EAO400L	Dahua 55 inch Wall-mounted LCD Digital Signage

**Dimensions (mm)**

