

# DHI-PKC-MS1C

## Mobile Stand



- Anti-collision function
- Wired remote control
- Double motor
- "Pull & release" brackets for easy mounting of display
- IFP controls lifting

### Series Overview

MS Series mobile stands are simple and elegant, allowing whiteboards to be conveniently moved.

### Technical Specification

#### Physical Specifications

Dimension of the assembled (L*W*H)	1036 mm × 738 mm × (1231-1731) mm (40.79" × 29.06" × [48.46"–68.15"])
Dimension with Package (L×W×H)	1124 mm × 818 mm × 189 mm (44.25" × 32.20" × 7.44")
Power Requirements	100–240 VAC
Lifting Distance	500 mm (19.69")
Gross Weight	35.5 kg (78.26 lb)
Net Weight(include wall mounts)	31.4 kg (69.23 lb)
Largest Bearing	100.0 kg (220.46 lb)
Applicable Model size	55"; 65"; 75"; 86"
VESA	800 mm × 600 mm (31.50" × 23.62")
Speed	25 mm/s
Control Mode	Control Panel; Control Pad; Software
Castors	4 inches mute
Color	Black

### Accessories

AC Power Cable (been installed)	1
USB Adapter Cable	1
Hand Controller	1
Screw Accessory Package	2
Installation Manual And Instruction For Use	1

### Environmental Conditions

Operation Temperature	0 °C to 40 °C (32 °F to 104 °F)
Operation Humidity	10%–90% (RH)
Storage Temperature	–20 °C to +60 °C (–4 °F to +140 °F)
Storage Humidity	10%–90% (RH)
Altitude	Below 2000 meters

### Ordering Information

Type	Model	Description
Mobile Stand	DHI-PKC-MS1C	Mobile Stand

Dimensions (mm[inch])

