



## DVI-IN2-F16

2-Channel DVI Input Card

| DVI



DVI-IN2-F16 is a two-channel DVI input card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The DVI-IN2-F16 inputs two DVI signals into the chassis

### FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel)  
DVI Rev. 1.0



# KRAMER

## TECHNICAL SPECIFICATIONS

---

PORTS:	2 DVI-D on Molex 24-pin (F) connectors
BANDWIDTH PER CHANNEL:	1.65Gbps
TOTAL BANDWIDTH:	4.95Gbps
MAXIMUM RANGE:	15m (49ft)
3D PASS THROUGH:	Not supported
POWER CONSUMPTION:	1.6W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
STANDARD COMPLIANCE:	DVI 1.0
SAFETY REGULATORY COMPLIANCE:	CE, FCC
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
Product Dimension	19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79" ) W, D, H
Product Weight	0.1kg (0.3lbs) approx
Shipping Dimension	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05" ) W, D, H
Shipping Weight	0.3kg (0.6lbs) approx