

EDC 1024 Flush Mount Delegate Unit



- Permanent flush-mounted microphone with ABS material
- Features a electrets Condenser stem microphone
- Provides Fixed/Pluggable gooseneck microphone for easier installation and maintenance
- BXB gooseneck microphones adopt DIN type plug preventing bad contact of the connector
- Gooseneck microphone with illuminating red ring to indicate speaking status
- Has 2* stereo earphone jacks for recording.
- Auto-Test functionality.
- Digital Series- parallel daisy-chain connected. Even though one of them is failed, just removes the failed one and then re-connected, the functionality still works perfectly.
- Provides Stem length: 43/48/56/70 cm.

TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
Sensitivity	≥ -50dB
Total Harmonic distortion	≤ 0.1%
S/N ratio	≥ 70dB
Voltage	DC 12V~18V
External speaker	MODEL : WM-02D
Unit Size	3"×1.5"
Capacity	2 W
Max sound pressure	92dB
Connections	9P D type plug , for system link, 9P cable (2.5M & 12M)
Auto Gain Control (AGC)	-45 ~ 0dB
Earphone jack	3.5Ø Stereo
REC jack	3.5Ø Stereo
Height × Width × Depth	146 × 62 × 114 (mm)
Weight	500g
Material	ABS special plastic
Surface	Anti-dirty plastic sticker

*The appearance and specifications of all item are subject to change without notice