

# EDC-2011/2012

## Table-top Chairman / Delegate Unit



### Product Features

- ▶ Featured with a built-in 2.5" monitor speaker. When the microphone is operated, the speaker would be auto-off to avoid sound feedback.
- ▶ No limitation of chairman unit's quantity; you can also randomly change the position and sequence.
- ▶ Built-in microphone voice sensor for automatic turn-off.
- ▶ Built-in recording output to simply reserve meeting minutes.
- ▶ Built-in headphone output (volume adjustable).
- ▶ Pluggable gooseneck microphone with shield and flexible tube for easy installation and maintenance (length provided: 43/48/56/70cm).
- ▶ Gooseneck microphone with illuminating red ring to indicate speaking status.
- ▶ Prevents the interference of electromagnetic wave.



### Hardware Specifications

Connection	RJ45 double port
Earphone OUT	Φ3.5 stereo x 1
Recording OUT	Φ3.5 stereo x 1
Frequency	100Hz-10KHz
Response	
Sensitivity	≥ -47dB +-3dB
Total Harmonic	≤ 0.15%
Distortion	
S/N Ratio	≥ 58dB
Max. Input Level	100dB @ Frequency=1KHz, THD < 5%



### Physical Dimension

Unit Size (DWH)	142 x 150 x 65(mm)
Weight	700g (not including mic)
Operation Temperature	0°C -40°C
Storage Temperature	-15°C- 55°C
Relative Humidity	45%-70% (non-condensing)
Air Pressure	86KPa-106KPa



### Power Supply

Supply Voltage	DC 18V
Standby Current	≈ 30mA

**IBXB**

BXB Electronics Co., Ltd.  
(Headquarter in Kaohsiung, Taiwan)

A : Rm. 1, 6F., No.288-5, Xinyu Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan (R.O.C.)

T : +886 7 9703838

F : +886 7 9703883

E : bxb@bxb.tw

www.bxb.tw