

EDC 1011 Table-top Chairman Unit



- Features a built-in 2.5 inches high-fi loudspeaker and electrets Condenser stem microphone
- Provides Fixed/Pluggable gooseneck microphone for easier installation and maintenance
- BXB gooseneck microphones adopt DIN type plug preventing bad contact of the connector
- Gooseneck microphone with illuminating red ring to indicate speaking status
- Chairman Unit can be linked anywhere within the chain, max. up to **10**
- Chairman features having "Priority" speak button to override delegate and the alarm sound when delegate-off
- Has 1* stereo earphone jack for recording.
- Has dust/wind-proof functionality to prevent it from sound explosion
- Loudspeaker is automatically switched off when the microphone is activated to prevent acoustic feedback
- Auto-Test functionality
- Digital Series- parallel daisy-chain connected. Even though one of them is failed, just removes the failed one and then re-connected, the functionality still works perfectly
- Provides Stem length: 43/48/56/70 cm

TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
Sensitivity	≥-50dB
Total Harmonic distortion	≤0.1%
S/N ratio	≥70dB
Voltage	DC 12V~18V
Build-in speaker	Unit size : 2.5", Capacity : 0.5W Max sound pressure : ≥92dB
Speaking Indicator Lamp	Illustrated Red Ring Light
Connection	1* 9P D type plug , for system link 9P cable (2.5M & 12M)
AGC (Auto Gain Control)	45 ~ 0dB
Earphone jack	3.5Ø Stereo
Height × Width × Depth	53.6 × 169.3 × 131.8 (mm)
Weight	831 g
Base	Zinc-Aluminum Alloy Diecast & Anti-slip mat
Top	ABS special plastic, , Modern Black color

*The appearance and specifications of all item are subject to change without notice