



KRAMER

F610-IN2-F16

2-Channel DVI over Ultra Reach 4LC Fiber
Input Card



F610-IN2-F16 is a two-channel DVI over 4LC fiber input card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The F610-IN2-F16 inputs two DVI over 4LC fiber signals into the chassis

FEATURES

Max. Data Rate - 6.75Gbps (1.65Gbps per graphic channel)

System Range - Up to 400m (1310ft) using Multi Mode OM2 fiber

Compatibility - Kramer 610R/T detachable optical transmitter and receiver over LC optical cable

Fiber Optics - Multi-mode fiber optic cable with 4 simplex or 2 duplex LC fiber connectors

Connectors - 4 LC optical connectors for R, G, B & clock



KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	2 4LC ports
BANDWIDTH PER CHANNEL:	1.65Gbps
TOTAL BANDWIDTH:	6.75Gbps
MAXIMUM RANGE:	400m (1310ft) using Multi Mode OM2 fiber
3D PASS THROUGH:	Not supported
POWER CONSUMPTION:	2.8W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
STANDARD COMPLIANCE:	DVI 1.0
SAFETY REGULATORY COMPLIANCE:	CE, FCC
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
Product Dimension	19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79") W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimension	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
Shipping Weight	0.4kg (0.8lbs) approx