

FC-4001

MultiCoder® Universal Analog & Digital Format Video Transcoder & TBC



The FC-4001 is a high-performance broadcast quality, universal video transcoder for analog and digital video signals. It converts a composite video, s-Video (Y/C), component video (RGB/S) or SDI video signal to either component or composite and s-Video (Y/C) video signals and to two SDI video signals

FEATURES

Bandwidth - 5MHz (-0.5dB)

Decoding Options Based on Signal Standard - Decodes 525-line signals to NTSC 3.58 or NTSC 4.43 and 625 lines to PAL-B/M/N & SECAM

Looping Analog Sync Input

Freeze Frame

Control Options - Front panel, RS-232

Selectable Sync Signal Termination

Built-in Time Base Corrector - Stabilizes sync in video sources

Timing Controls - SCH phase & sync phase

Front Panel Lockout

Worldwide Power Supply - 100-240V AC



TECHNICAL SPECIFICATIONS

INPUTS: 1 composite video, $1Vpp/75\Omega$ on a BNC connector; $1 Y/C 1Vpp/75\Omega$ (Y),

> $0.3\text{Vpp}/75\Omega$ (C) on a 4-pin connector; 1 component video Y/R-Y/B-Y, $1\text{Vpp}/0.7\text{Vpp}/0.7\text{Vpp})/75\Omega$ (or RGB/S) on BNC connectors; 1 SDI on a BNC

connector; 1 genlock with loop, $75\Omega/Hi-Z$ on BNC connectors

OUTPUTS: 1 composite video, $1Vpp/75\Omega$ on a BNC connector; 1 Y/C, $(Y) 1Vpp/75\Omega$, and (C)

 $0.3Vpp/75\Omega$ on BNC connectors; 1 component or RGB/S video,

 $1\text{Vpp}/0.7\text{Vpp}/0.7\text{Vpp}/75\Omega$ on BNC connectors; 2 SDI on BNC connectors

VIDEO STANDARDS: PAL-B/D/G/H/I/M/N, NTSC-3.58/4.43, SECAM

DIGITAL

RESOLUTION:

10 bits

BANDWIDTH: -0.5dB to 5MHz

DIFF. GAIN: 1%

DIFF. PHASE: 1Deg

K-FACTOR: 1%

S/N RATIO: 63dB

LUMA NON-

LINEARITY:

1%

CHROMA/LUMA

DELAY:

1ns

CONTROLS: Front-panel and RS-232; SCH phase, SYNC phase, H shift, freeze, panel lock

POWER

CONSUMPTION:

230V AC, 50/60Hz (115V AC, USA), 14VA

INCLUDED

ACCESSORIES:

Power cord, null-modem adapter, rack "ears"

PRODUCT

19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.0kg (0.0lbs) approx

SHIPPING DIMENSION: 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

SHIPPING WEIGHT: 2.6kg (5.7lbs) approx

