



## FC-6P

2-Port Multi-Function Serial/IR PoE Control Gateway

| Ethernet - RJ-45



FC-6P is a serial/IR multi-function control gateway with Power over Ethernet, capable of plug and play deployment over a customer Ethernet LAN for remote bidirectional RS-232 or RS-485 and IR emitter control of customer devices. Multiple control clients can be IP-connected to the FC-6P control gateway for concurrent control of two RS-232 or four IR controllable devices, such as AV scalars, video displays, audio amplifiers, and DVD players

### FEATURES

**Dual-Function I/O Ports** - Remote IP-Based control of devices connected to the control gateway dual-function I/O ports, with selectable port configuration to bidirectional RS-232, RS-485 or IR control

**Multiple IP Connected Clients** - Remotely connected over customer Ethernet network, concurrently controlling any devices connected to control gateway I/O ports

**Easy & Reliable Installation** - With single PoE cable for both, powering and connectivity, and Plug and Play IP installation with dynamic (DHCP) address resolution and auto device discovery over customer LAN. Highly-resilient powering with multiple power options — USB, Power over Ethernet per IEEE 802.3af standard, and optional PSU (not included). Compact, designed for piggy-back installation, such as behind a TV or display, with the ability to draw power from device USB port and Ethernet connectivity

**Remote Management** - Built-in web UI for remote browser-based management and support, by multiple IP-clients over customer LAN. Easy firmware upgrades, either remotely via customer LAN, or locally via device USB port



## TECHNICAL SPECIFICATIONS

---

PORTS:	2 RS-232/IR multi-function ports on 3-pin terminal blocks, each selectable as one of: - 1 bidirectional RS-232 (RS-485 port 1 selectable option) serial - 2 IR emitter ports, 1 Ethernet on an RJ-45 female connector, 1 built-in IR sensor for learning, 1 mini USB connector for local services
SUPPORTED SERIAL PORT BAUD RATES:	1200, 2400, 4800, 9600, 19200, 38400, 57600, 15200bps
RS-232 COMMUNICATION:	Transparent up to 115200bps
IR EMITTER CABLE RANGE:	80m (260ft)
SUPPORTED IR OUTPUT FREQUENCIES:	20kHz to 1.2MHz
SUPPORTED IR INPUT FREQUENCIES:	20kHz to 60kHz
MAXIMUM DATA HANDLING OF DEVICE:	Up to 150kbps (summed on all ports, see Section 7.1)
MAXIMUM SIMULTANEOUS IP-CLIENT CONNECTIONS:	40
POWER SOURCE:	5V DC, 2A
POWER CONSUMPTION:	5V DC, 250mA
ENCLOSURE TYPE:	Tools, Aluminum
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50" ) W, D, H
SHIPPING WEIGHT:	0.8kg (1.8lbs) approx
COOLING:	Convection ventilation
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	3ft USB cable, bracket set
OPTIONAL ACCESSORIES:	Power supply unit, RK-3T rack adapter
RACK MOUNT:	With optional RK-3T rack adapter
VIBRATION:	ISTA 1A in carton (International Safe Transit Association)

SAFETY REGULATORY COMPLIANCE: CE

ENVIRONMENTAL REGULATOR COMPLIANCE: Complies with appropriate requirements of RoHs and WEEE