



## FC-6

### 2-Port Multi-Function Serial/IR Control Gateway

| Ethernet - RJ-45



FC-6 is an RS-232/IR multi-function control gateway, capable of plug and play deployment over a customer Ethernet LAN for remote bidirectional RS-232 and IR emitter control of customer devices. Multiple control clients can be IP-connected to the FC-6 control gateway for concurrent control of two RS-232 or four IR controllable devices, such as AV scalers, video displays, audio amplifiers, and DVD players

## FEATURES

**Dual-Function I/O Ports** - Remote IP-Based control of devices connected to the control gateway dual-function I/O ports, with selectable port configuration to bidirectional RS-232 or IR control

**Multiple IP Connected Clients** - Remotely connected over customer Ethernet network, concurrently controlling any devices connected to control gateway I/O ports

**Easy & Reliable Installation** - Plug and Play IP installation with dynamic (DHCP) address resolution and auto device discovery over customer LAN. Resilient powering with USB and optional PSU (not included). Compact, designed for piggy-back installation, such as behind a TV or display, with the ability to draw power from a device USB port

**Remote Management** - Built-in web UI for remote browser-based management and support, by multiple IP-clients over customer LAN. Easy firmware upgrades, either remotely via customer LAN, or locally via device USB port

**Pico TOOLS™** - Mount 4 units side-by-side in a 1U rack space with the recommended rack adapter



## TECHNICAL SPECIFICATIONS

---

PORTS:	2 RS-232/IR multi-function ports on 3-pin terminal blocks, each selectable as one of: <ul style="list-style-type: none"><li>- 1 bidirectional RS-232 serial</li><li>- 2 IR emitter ports,</li></ul> 1 Ethernet on an RJ-45 female connector, 1 built-in IR sensor for learning, 1 mini USB connector for local services
SUPPORTED SERIAL PORT BAUD RATES:	1200, 2400, 4800, 9600, 19200, 38400, 57600, 15200bps
RS-232 COMMUNICATION:	Transparent up to 115200bps
IR EMITTER CABLE RANGE:	80m (260ft)
SUPPORTED IR OUTPUT FREQUENCIES:	20kHz to 1.2MHz
SUPPORTED IR INPUT FREQUENCIES:	20kHz to 60kHz
MAXIMUM DATA HANDLING OF DEVICE:	Up to 150kbps summed on all ports
MAXIMUM SIMULTANEOUS IP-CLIENT CONNECTIONS:	40
POWER SOURCE:	5V DC, 2A
POWER CONSUMPTION:	5V DC, 300mA
ENCLOSURE TYPE:	Pico Tools, aluminum
COOLING:	Convection ventilation
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	3ft USB cable, bracket set
OPTIONAL ACCESSORIES:	Power supply unit
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
Product Dimensions	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H
Product Weight	0.1kg (0.2lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
Shipping Weight	0.3kg (0.6lbs) approx