



## FC-7

### 2-Port Multi-Function GPIO/Relay Control Gateway

| Ethernet - RJ-45



FC-7 is a compact GPIO/relay multi-function control gateway, capable of plug and play deployment over a customer Ethernet LAN for remote GPIO and relay control of customer devices. Multiple control clients can be IP-connected to the FC-7 control gateway for concurrent control of devices such as lights, shades and screens

## FEATURES

**Dual-Function I/O Ports** - Remote IP-Based control of devices connected to the control gateway dual-function I/O ports, with selectable port configuration to bidirectional GPIO or relay control

**Multiple IP Connected Clients** - Remotely connected over customer Ethernet network, concurrently controlling any devices connected to control gateway universal I/O ports

**Easy & Reliable Installation** - With Plug-and-Play IP Installation with dynamic (DHCP) address resolution and auto device discovery over customer LAN. Compact, designed for piggy-back installation, such as behind a TV or display, with the ability to draw power from device USB port and Ethernet connectivity

**Remote Management** - Built-in web UI for remote browser-based management and support, by multiple IP-clients over customer LAN. Easy firmware upgrades, either remotely via customer LAN, or locally via device USB port



# KRAMER

## TECHNICAL SPECIFICATIONS

|   |  |
|---|--|
| PORTS:                                      | 2 GPIO/relay multi-function ports on 3-pin terminal blocks, each selectable as one of:<br>– 2 GPI/O ports<br>– 1 relay port,<br>1 LAN on an RJ-45 female connector,<br>1 mini USB connector for local services |
| MAXIMUM SIMULTANEOUS IP-CLIENT CONNECTIONS: | 40   |
| POWER SOURCE:                               | 5V DC, 2A  |
| POWER CONSUMPTION:                          | 5V DC, 370mA   |
| ENCLOSURE TYPE:                             | Pico Tools, aluminum   |
| COOLING:                                    | Convection ventilation   |
| OPERATING TEMPERATURE:                      | 0° to +40°C (32° to 104°F)   |
| STORAGE TEMPERATURE:                        | -40° to +70°C (-40° to 158°F)  |
| HUMIDITY:                                   | 10% to 90%, RHL non-condensing   |
| INCLUDED ACCESSORIES:                       | 3ft USB cable, bracket set   |
| VIBRATION:                                  | ISTA 1A in carton (International Safe Transit Association)   |
| SAFETY REGULATORY COMPLIANCE:               | CE   |
| ENVIRONMENTAL REGULATORY COMPLIANCE:        | Complies with appropriate requirements of RoHs and WEEE  |
| PRODUCT DIMENSION:                          | 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H  |
| PRODUCT WEIGHT:                             | 0.1kg (0.2lbs) approx  |
| SHIPPING DIMENSION:                         | 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H  |
| SHIPPING WEIGHT:                            | 0.3kg (0.6lbs) approx  |

