

FCS 3026

Flush-Mounted Delegate Unit



- **Stylish Aluminum Extrusion**
- **Advanced Cat 5e Cabling**
- Delegate unit can be linked anywhere within the chain (Max 999 Delegate units)
- Features electrets condenser stem microphone
- "Talk" button to activate/deactivate microphone
- Stereo earphone jack*1; Rec*1
- Volume Control
- BXB gooseneck microphones adopt DIN type plug preventing bad contact of the connector
- Pluggable gooseneck microphone
- Illuminated red light ring for easy identification of speaker
- Quick access to "Chairman" mode
- Automatic test function
- Stem length: 43/48/56/70 cm (17", 18.9", 22", 27.6")
- Digital Series- parallel daisy-chain connection.
- MIC Auto-Off: 10-99 seconds

Information

BXB ELECTRONICS CO., LTD

TEL : +886(7)970-3838

FAX : +886(7) 970-3883

Email: bxp@bxp.tw

<http://www.bxp.tw>

6F-1, No.288-5, Shin Ya Road,
Chien Chen District,
Kaohsiung, Taiwan, R.O.C.
80673



TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
Sensitivity	≥ -50dB
Total Harmonic distortion	≤ 0.1%
S/N ratio	≥ 70dB
Voltage	DC 12V~18V
Connections	RJ-45 Jack x 2 (2.5M/20M Cat 5e)
Auto Gain Control (AGC)	-45 ~ 0dB
Earphone jack	3.5Ø Stereo
REC jack	3.5Ø Stereo
Height x Width x Depth	75 x 170 x 43 (mm)
Weight	346g w/o microphone
Material	Galvanized sheet steel
Surface	Aluminum extrusion