



# KRAMER

## Galil 5-O

5.25-Inch, 2-Way On-Wall Speakers

| Speakers



The Galil 5-O On-wall Speaker features a multi-tap power transformer for selecting  $8\Omega$  (bypassing the transformer) or 70V/100V power settings that are suitable for an array installation. Available in white

### FEATURES

Type - 2-way on-wall speaker

Woofer - 5.25" polypropylene cone

Tweeter - 0.5" Mylar dome

Impedance -  $8\Omega$

Power Handling - 30W RMS, 80W continuous program

Transformer Taps - 70V - 20W/10W/5W/2.5W/Off (Lo-Z), 100V - 20W/10W/5W/Off (Lo-Z)

Package - 2 speakers (1 pair)



# KRAMER

## TECHNICAL SPECIFICATIONS

---

DESCRIPTION:	2-way on-wall speakers
FREQUENCY RESPONSE:	80Hz to 20kHz @-10dB, 100Hz to 20kHz @±3dB
WOOFER:	5.25" (133mm) polypropylene cone
TWEETER:	0.5" (13mm) Mylar
IMPEDANCE:	8Ω (transformer tap in off position)
TRANSFORMER TAPS:	70V – 20W/10W/5W/2.5W/Off (Lo-Z), 100V – 20W/10W/5W/Off (Lo-Z)
SENSITIVITY:	89dB 1W @1m
MAX SPL:	Continuous: 103dB, peak: 106dB
POWER HANDLING:	30W RMS, 80W continuous program
CROSSOVER FREQUENCY:	7.2kHz
DIRECTIVITY FACTOR (Q):	4.0, averaged 1kHz to 10kHz
DIRECTIVITY INDEX (DI):	6.0 dB averaged 1kHz to 10kHz
INPUT CONNECTORS:	Terminal blocks
MATERIALS:	Frame, grill and brackets steel; cabinet ABS
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
WEIGHT PER SINGLE SPEAKER:	2kg (4.4lbs) approx
WEIGHT WITH MOUNTING KIT:	2.4kg (5.3lbs) approx
SHIPPING WEIGHT (FOR PAIR):	4.8kg (10.6lbs) approx
DIMENSIONS with mounting brackets:	18.5cm x 16.7cm x 27cm (7.28" x 6.6" x 10.6"), W, D, H
INSTALLATION CLEARANCE:	Front panel to wall (with mounting bracket): 21cm (8.2"), back panel to wall (with mounting bracket): 4.5cm (1.8")
ACCESSORIES:	2 mounting brackets (including 4 knobs and 4 mounting screws)
OPTIONS:	BCP-2S speaker cable
COLOR:	Available in white