HDS-720 Network AV Controller







Product Features

- ▶ IP Camera Control and Setting: set and save the preset points of BXB HDC-713 & HDC-715 IP Camera. Support 1011 preset points (conference unit x 1009 + HOME x 2 + panorama view) and control the maximum of 16 cameras.
- ▶ Intuitive Web Interface: you can configure the system settings and control & monitor the camera's images on the web browser via the PC or mobile devices.
- ▶ Equipped with RS-232 port: connect with BXB UFO-2050, EDC-2051, and FCS-6350 Conference MCU to control the camera.
- ► Equipped with RS-485 port: connect with BXB HCK-700 Compact Camera Controller to control the camera.
- ▶ Equipped with RJ45 port: connect with BXB FCS-6350 Conference MCU to control the camera via Internet.
- ▶ Equipped with HDMI OUT port: for video live streaming and seamless switch of camera images.



Hardware Specifications

Internet RJ45 TCP/IP port x 1

Video Output HDMI x 1

Audio Output Φ3.5 linear source x 1

IN x 1

USB USB2.0 x 2
RS-485 Control RS-485 x 1
RS-232 Control RS-232 x 1



N.O. Trigger

Physical Specifications

Dimensions 45*485*105 (mm)

 $(L \times W \times H)$

Weight 1.15KG (power supply

not included)

Rack Mount 19" 1U



Power Supply

External Power DC 5V-2A MAX

Supply

Voltage/Frequency 110/220V Power Consumption 10W Weight of Power 0.1KG

Supply



A: Rm. 1, 6F., No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan (R.O.C.)

: + 886 7 9703838 **F** : + 886 7 9703883

E:bxb@bxb.tw www.bxb.tw