

## HT-ASPo8 Hitrolink Integrated Speaker



## **Features**

- 5-in-1 multi-functional design, without additional configuration, to meet the needs of conference room speech reinforcement and multimedia Play. Integrated Amplifier, Audio Processor, Wireless Microphone, Speaker, Remote Control.
- Support remote configuration and diagnose via network
- Built-in professional Audio Processor Algorithm. Support automatic Audio Mixing function, with Audio Mixing component control function, feedback cancellation, Echo Cancellation and Noise cancellation.
- Enter per Channel: pre-amplifier, signal generator, expander, compression device, and 5-segment parameter equalizer.
- Output per channel: 31 segments of graphic equalizer, delayer, frequency divider and limiter.
- Packaged with 2 channel UHF wireless inputs, can extend 4 analog inputs, and 4 analog outputs
- Applicable to 50 ~ 100 m² meeting rooms, training classrooms and other small-to-large conference rooms

Technical Parameter		
Speaker Parameter	Frequency response range	60-20KHz
	Impedance	8Ω
	Sensitivity	94dB
	Rated Power	150W
	Peak Power	300W
	Max. Sound Pressure Level	106dB
	Unit configuration	8-inch 50-core 140 magnetic woofer, 34-core horn tweeter
	Speaker material	15 mm high quality splint
	Divergence angle	(H×V): 100° (H) ×50° (V)
	Dimension (H * W * D)	479*266*290mm
	Net weight	12kg(Main speaker); 11kg(Sub speaker)
	Gross Weight	15.1kg(Main speaker); 13kg(Sub speaker)
Device function Parameter	Frequency Range	610-690MHz
	Wireless reception Sensitivity	108dBm @12dB SINAD
	Power amplifier Output	2x150W @ 8Ω
	Analog Channel Background Noise	-86dBu
	Frequency Response	-1.6dBu @20 ~ 20kHz
	Amplifier Total Harmonic Distortion (THD) (THD + N)	≤0.02% @1kHz, 1W
	Enter Output Quantization	48KHz/24bit
	Analog Maximum Gain	48dB
	Input CMRR	70 dB @60Hz
	Analog Input Impedance	$20$ k $\Omega$ balance, $10$ k $\Omega$ unbalance
	Channel isolation	>100dB

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

