

J2630Z

1080P Box Camera

12x Optical Zoom / LAN+3G-SDI / PoC+PoE



Product Features

● 1080P Full-HD

The 1/2.8-inch quality HD CMOS sensor with effective 2.07 megapixels offers HD quality images up to 1920x1080 pixels.

● 72.5° Wide-angle Lens + 12X Optical Zoom

72.5° ultra-wide-angle lens with 12x optical zoom.

● POC and POE Supported

POC (Power Over Cable) and POE (Power Over Ethernet) supported; power supply, video, audio and control are integrated; the transmission distance of 1080P HD content is over 100 m.

● RS485 Remote Control

R485 port is used to remotely control all parameters of camera.

● HD Digital Interface

The 3G-SDI offers an effective transmission distance up to 100 m (1080p30). SDI and network outputs are supported simultaneously.

● AAC Audio Encoding

AAC is supported for better sound quality and reduced bandwidth hogging.

● Jack

Audio I/O is supported to meet various requirements of customers.

● Network Interface Video Output

Network-based multiple Video stream outputs (bit stream No. 1 and bit stream No. 2) are supported.

● Low Illumination

The application of 2D and 3D noise reduction algorithm greatly reduces image noise. Even under the condition of ultra-low illumination, it still keep the picture clean and clear, and the SNR of image is as high as 55dB.

Product Specifications

Camera

Signal System	1080p/60, 1080p/50, 1080i/60, 1080i/50, 1080p/30, 1080p/25, 720p/60, 720p/50,
Sensor	1/2.8 inches, CMOS, Effective Pixels: 2.07 Megapixels
Scanning Mode	Progressive
Focal length	12x, f=3.5mm ~ 42.3mm, F1.8 ~ F2.8
Minimum Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual, VAR
Backlight Compensation	Support
Digital Noise Reduction	2D & 3D Digital Noise Reduction
SNR	≥ 55dB
Horizontal FOV	72.5° ~ 6.9°
Vertical FOV	44.8° ~ 3.9°
Inverted Installation	Support
Preset Position	255
PoC	Support
PoE	Support

Interfaces

HD Output	1x 3G-SDI: BNC , 800mVp-p, 75Ω, as per SMPTE 424M standard
Network Interface	1x RJ45: 10M / 100M adaptive Ethernet
Audio Interface	1x LINE IN, 3.5mm Jack
Control Interface	1x RS-485: 3-core honeycomb interface; max. distance 1200 m; VISCA/Pelco-D/Pelco-P protocols
Power Interface	DC005 type (DC IN 12V) / PoC / PoE (802.3af)

General Specifications

Input Voltage	DC 12V / POC / POE (802.3af)
Input Current	0.5A (Max.)
Operating Temperature	-10° C ~ 40° C
Storage Temperature	-40° C ~ 60° C
Power Consumption	6W (Max.)
Dimension	142mm x 77mm x 72mm
Net Weight	0.7Kg



Network Features

Video Compression	H.264 / MJPEG
Video Stream	First Stream, Second Stream
First Stream Resolution	1920x1080, 1280x720, 1024x576 etc.
Second Stream Resolution	1280x720, 720x576, 720x480, 320x240 etc.
Video Bit Rate	32Kbps ~ 2048Kbps
Bit Rate Control	VBR, CBR
Frame Rate	50Hz: 1fps ~ 25fps, 60Hz: 1fps ~ 30fps
Audio Compression	AAC
Audio Bit Rate	96Kbps, 128Kbps, 256Kbps
Protocols	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.