



kramer

K-Speak

Omni-directional Speaker Phone, 6
Microphone Array, Bluetooth/USB/Aux
Connectivity, and Wireless Charging



Omnidirectional, compact speakerphone for crystal-clear sound

Ensure all meeting participants are heard clearly from every seat in the room. With 360° omnidirectional audio pickup, high-fidelity sound and simple operation, the K-Speak enhances the audio experience for everyone – whether in the room or joining remotely. The small size and multiple connection options are a perfect fit for huddle rooms and small meeting rooms, where table space is at a premium

FEATURES

Fast setup, flexible configuration -

Fast setup and installation – Connect via AUX, Bluetooth, Bluetooth dongle or USB
Can be connected to the K-180Mini via USB for seamless full-room audio and video
Two K-Speak speakerphones can be connected, to cover larger tables
Optional wireless charging – Reduces tabletop clutter

Crystal-clear sound -

6-element microphone with voice pickup radius of 5m (16.4 ft)
Noise and echo cancelation
Up to 8 hours operation

Optional - K-SPEAK-5YW comes with a 5-year warranty at a price of \$357



kramer

TECHNICAL SPECIFICATIONS

Ports	1 AUX In/Out: On a 3.5mm mini jack 1 Audio In/Out + 5V/2A charging: On a USB-C connector Bluetooth: BT4.2+EDR
Microphone	Type: 6-element Microphone array Pickup Distance: Up to 5 meters Frequency: 150Hz~8kHz Sensitivity: -38dBV Signal-to-noise Ratio: 65dB
Speaker	Maximum Sound Pressure Level: 80dB SPL@1m Distortion: $\leq 4\%$ @150Hz~16kHz Signal-to-noise Ratio: $\geq 75\text{dB}@1\text{m}$ Frequency Response: 150Hz~16kHz
Controls	Buttons: Power, answer/hang up, mute, Bluetooth, volume +, volume - Indicator lights: Power, Volume, Bluetooth, Mute, Answer/Hang up Modes: Music mode/caCl mode (under Bluetooth mode)
Battery	Battery Capacity: 7.4V/2200mAh Charging Requirement: Wired: 5V, 1.5A, Wireless: 5W Battery Life on a Single Charge: Up to 8 hours
Environmental Conditions	Operating Temperature: -5° to +40°C (23° to 104°F) Storage Temperature: -20° to +60°C (-4° to 140°F) Humidity: 10% to 90%, RHL non-condensing Altitude: Below 5000 meters
Regulatory Compliance (Standards Compliance)	Safety: CE, FCC Environmental: RoHs, WEEE
General	Net Dimensions (Diameter, H): 12cm x 3.5cm (4.7" x 1.4") Shipping Dimensions (W, D, H): 15.8cm x 22.2cm x 4.8cm (6.2" x 8.7" x 1.9") Net Weight: 0.4kg (0.9lbs) approx Shipping Weight: 0.71kg (1.6lbs) approx
Accessories	Included: 1 USB Type-C cable, 1 AUX 3.5mm cable, 1 USB dongle
Product Dimensions	12.00cm x 12.00cm x 3.50cm (4.72" x 4.72" x 1.38") W, D, H
Product Weight	0.4kg (0.9lbs) approx

Shipping Dimensions 15.80cm x 22.20cm x 4.80cm (6.22" x 8.74" x 1.89") W, D, H

Shipping Weight 0.7kg (1.6lbs) approx

