

K50 Specification

Main Features	<p>1) Support network control, with independent IP address.</p> <p>2) Support VISCA, ONVIF protocol, and VISCA fully compatible.</p> <p>3) Realize the control of conference camera software, with central control function.</p> <p>4) It adopts imported variable speed four-dimensional rocker for control, and feels comfortable. The twisting rocker can control zoom in and out and directly control the omnidirectional rotation of the conference camera. According to the strength on the joystick, the speed can be controlled.</p> <p>5) The zoom control of the conference camera is carried out by a switch shaping like a ship. Operation is convenient and powerful.</p> <p>6) Support full-key backlight effect, can be turned on / off independently.</p> <p>7) Support IE browser to add configuration front-end device parameters.</p>
Model	K50
Name	Keyboard Controller
Parameter	
Interfaces	RS422, RS232, network, USB2.0
Protocol	VISCA, ONVIF2.4
Display mode	LCD
Power	Power supply: DC 12V-2A
	Power consumption: 6W (max)
Size	Dimension (mm): 320*177*115.5 (mm)
Working Environment	Environmental Temperature: 0°C~55°C / 14°F~131°F
	Humidity: 20~80%(No-Condensation)
Storage Environment	Environmental Temperature: -10°C~60°C / 14°F~140°F
	Humidity: 0~90%(No-Condensation)
Warranty	1 year

