

## KDS-DEC3

H.264 Decoder

| HDMI | Ethernet - RJ-45





Kramer KDS-DEC3 is an H.264 decoder for encoded signals up to 1080p60. It is designed to work with the KDS-EN3 H.264 encoder to provide a high-quality and fully-featured end-to-end video and audio over IP solution

## **FEATURES**

AVC Support - MPEG-4 using H.264 & AAC codecs

Scaling & Cropping Features - For flexible display of source content on the decoder output Standard Ethernet Network Operation - 10/100/1000Mb

Decoder-Integrated Network Switch - Allows for KDS-DEC3 daisy chaining and network extension

Video Support - HDMI

Audio Support - HDMI or analog

Streaming Support - Unicast and multicast through RTSP (Real Time Streaming Protocol)

KDS-EN3 Manager Software - Allows remote management of the KDS-EN3 network including auto-detection and discovery of KDS-EN3/KDS-DEC3 units on a subnet

Fail-safe Video Playback - When a decoder loses its connection to an encoder

RS-232 Virtualization - From encoder to decoder



## TECHNICAL SPECIFICATIONS

**OUTPUTS:** 1 HDMI, 1 unbalanced stereo audio on a 3.5mm mini jack

PORTS: 2 Ethernet on RJ-45 connectors (fully switched), 1 RS-232 on a 9-pin D-sub

connector

VIDEO SINGLE CHANNEL HD:

Up to 1920x1080p60 and 1920x1200(60Hz)

COMPRESSION

STANDARD:

H.264/Mpeg4 Part 10 (AVC)

PROFILES: Baseline, Main, High

LEVELS: Up to 4.2

BIT RATES: 100Kbps to 25Mbps

96, 128, 192, and 256Kbps

RATE CONTROL: CBR, VBR, adjustable GOP (Group Of Pictures) size

AUDIO

MPEG4 AAC-LC

COMPRESSION STANDARD:

CHANNELS: 2 channel (stereo), HDMI with digital L-PCM audio

ANALOG SAMPLE

FREQUENCY:

32, 44.1, and 48kHz

OUTPUT 1920×1200, 1920×1080, 1680×1050, 1600×1200, 1600×900, 1440×900,

**RESOLUTIONS:** 1400×1050, 1360×768, 1280×1024, 1280×960, 1280×720, 1024×768, 800×600,

720×576, 720×480, and 640×480

**POWER** 

CONSUMPTION:

5V DC, 3A max

**OPERATING TEMPERATURE**  0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE:  $-40^{\circ}$  to  $+70^{\circ}$ C ( $-40^{\circ}$  to  $158^{\circ}$ F)

**HUMIDITY**:

10% to 90%, RHL non-condensing

**INCLUDED** 

ACCESSORIES:

Power supply, power cord, plastic bracket set

**Product Dimensions** 

21.50cm x 10.00cm x 2.60cm (8.46" x 3.94" x 1.02") W, D, H

**Product Weight** 

0.3kg (0.6lbs) approx

Shipping Dimensions 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

Shipping Weight 1.2kg (2.6lbs) approx



