

KT-107S
Secured 7-Inch Wall & Table Mount PoE
Touch Panel

| Ethernet - RJ-45



KT-107S is a highly secured 7-inch IPS multi-touch, powerful touch panel with 1280x800 resolution. Elegantly designed for decorative room integration, this portable touch panel can be deployed either tabletop or on-wall, mounted inside standard in-wall junction boxes. KT-107S supports wired Power over Ethernet (PoE) resilient connectivity. The touch panel comes with table and wall mounts for easy installation, secured mounting, and flexible deployment. KT-107S is an Android-based touch panel that is ideal for any 24/7 Kramer-supported commercial AV or control application and features a user-friendly, fully customizable graphical user interface configured by Kramer software

FEATURES

High Security Operation - Touch panel specially designed for highly secured deployment applications, with no camera, microphone, Wi-Fi and Bluetooth wireless connectivity

Elegant Design - Smooth integration with room furniture design, either on table or wall, with flexible panel cabling and locking design options

Easy Installation - Single Ethernet cable for connectivity and powering, flexible package-included table and wall mounts that fit into standard market-available 2-gang in-wall junction boxes and simple wired USB peripheral add-on connectivity to either mounting options with package-included USB cable

Reliable Operation - Seamless, non-service affecting switching between PoE, PSU and battery powering resiliency options

Secured Deployment - Flexible, invisible panel and mounts, screwing and locking options to prevent unwanted displacement, secured applications operation with various unauthorized exit protection options

Hi-quality User Experience - IPS 1280x800 hi-resolution screen with ±80° horizontal and vertical wide viewing angles, built-in lighting sensor for auto-adaptable brightness, with advanced 10 multi-touch points and 2 finger gesture capabilities

Powerful Processing - Quad-core CPU, GPU, 2GB RAM, 16GB ROM processing performance, smoothly running complicated media and graphics rich applications, such as H.265 video and audio streams encoding and decoding

Flexible Services - Advanced Android 6.0 Operating System with rich Kramer and market-available applications from cloud/store offerings, such as K-Touch Control and EventBoard Scheduling applications



TECHNICAL SPECIFICATIONS

Tabletop Mount Ports: 1 1000/100/10BaseT Ethernet on RJ-45 connector, 1 micro USB 2.0, 2-pin

terminal block for DC power supply

On-Wall Mount Ports: 1 1000/100/10BaseT Ethernet on RJ-45 connector, 2-pin terminal block for DC

power supply

Speakers: $2x1W, 8\Omega$

CPU Performance: 1.6GHz Quad Core, GPU, 2GB RAM, 16GB flash

OS Software: Android 6.0.1

Multi Touch: 10 points, 2-finger gesture

Display: 7" IPS, 1280x800 RGB pixels, 16:10 aspect ratio, ±85° horizontal/vertical viewing

angles, 400cd/m2 brightness, 800:1 contrast ratio

Video Decoding

Format:

HEVC/H.265, H.264, H.263, MPEG-1/2/4, VC-1, VP6/8, RV8/9/10, AVS, MVC,

Sorenson Spark, M-JPEG

Video Encoding

Format:

H.264, MVC, VP8, M-JPEG

Ethernet Port: 10/100/1000Mbps PoE LAN

Battery: Rechargeable, supports up to 3 hours of offline operation

Controls: Hidden Reset button, power button (ON/OFF), volume up button

Touch panel status

LED:

Flashes green during charging, steady green for fully charged

Power Inputs: Power over Ethernet (complies with IEEE802.3af and IEEE802.3at PoE standards),

power supply unit

Power Consumption: 5V DC, 3A

Operating

0° to +40°C (32° to 104°F)

Temperature:

Storage Temperature: -10° to +55°C (14° to 131°F)

Humidity: 10% to 90%, RHL non-condensing

Case Design: Black body and cover

Included Accessories: Power supply unit adapter (5V, 4.0A AC/DC), tabletop mount, on-wall mount unit,

panel-mount plate, right-angle OTG USB cable, installation screws

Certifications: CE/CB, FCC, ROHS, REACH

Mounting Options: Table top (with docking station), on-wall (with mount unit and panel mount plate)

Product Dimensions 17.80cm x 13.00cm x 1.30cm (7.01" x 5.12" x 0.51") W, D, H

Product Weight 0.4kg (0.8lbs) approx

Shipping Dimensions $22.40cm \times 20.60cm \times 13.00cm (8.82" \times 8.11" \times 5.12") W, D, H$

Shipping Weight 1.8kg (4.0lbs) approx

