

M1000B

4K All-in-One Business USB Video Bar

4K / Integration Design / Audio 3A Algorithm / Intelligent Analysis



Product Features

● Application

It's designed for small and medium-sized conference rooms, especially huddle rooms with 4-6 people, and to help enterprises re-tap the potential of internal small and mini-sized conference rooms to hold conferences more efficiently and cut lease cost.

● Value

Convenient for small and medium-sized enterprises to flexibly carry out daily business talks and team collaboration remotely; creating relaxed, free and smooth communication for quick decision-making and efficiency improvement.

● Integration Design

The three-in-one design incorporating the 4K UHD camera, the beamforming microphone and the full-frequency speaker helps reduce wiring and makes available easy video communication.

● 4K UHD

1/2.5-inch UHD CMOS sensor with 8.51 megapixels offers 4K (3840x2160)@30fps UHD images, downward compatible with various resolutions such as 1080P and 720P to meet users' needs for different video experiences.

● Wide FOV

121° wide FOV (110° horizontal FOV), and 5x zoom; optical lenses tailored for video conferences; built-in electric tripod head horizontal and pitch $\pm 15^\circ$; easier for participants to be videoed.

● Rich Interfaces

HDMI 1.4b and USB3.0 supported; simultaneous output of UHD audios and videos is available.

● Easy to Deploy

Flexible installation such as desktop, wall-mount, and TV/ display mount are available for quick install and deploy in a crowded conference room.

● Beamforming Microphone

Built-in beamforming (BF) microphone, pickup distance is 6m; the low-distortion transverse beamforming algorithm guides the microphone to speaker for better sound effect and make communication more clear, full and true.

● Audio 3A Algorithm

The built-in audio 3A algorithm (AEC/AGC/ANS) and full-duplex mode meet the communication requirements of various rooms; people who sit at the conference table, sit or stand next to you can talk comfortably and clearly.

● Full-Frequency Speaker

The acoustically designed high-fidelity speaker minimizes interference and offers extraordinary sound effects.

● PnP

Connection to PCs or commercial large screens is realized through PnP USB ports; the out-of-the-box mechanism helps reduce wiring and offers easy-to-handle video communication, thereby lowering the user thresholds.

● Speakerphone

Mobile phones and other devices can connect to this device via Bluetooth and use it as Bluetooth microphone and loudspeaker, and to connect phone calls to audio and video conferences.

● Intelligent Analysis

Built-in intelligent analysis algorithm, voice recognition, participants automatic frame selection, speaker automatic tracking and switching speaker screen to ensure that the speaker is always clearly in the screen.

● Bluetooth 5.0

Using Bluetooth 5.0 technology, compared with the previous generation technology, the transmission speed is increased by 2 times, and the transmission distance is increased by 4 times. Better transmit the high-quality audio between mobile phone and tablet devices to achieve the wireless Bluetooth streaming.

Product Specifications

Camera

Signal System	4K/30, 1080p/30, 720p/30 etc
Sensor	1/2.5 inches, CMOS, Effective Pixels: 8.51 Megapixels
Optical Lens	121° (DFOV), 110° (HFOV), 75° (VFOV), 5x zoom Horizontal/pitch $\pm 15^\circ$
PTZ	Mechanical PTZ (MPT) + e-PTZ (EPTZ)
Digital Noise Reduction	2D & 3D Digital Noise Reduction
SNR	≥ 55 dB
Backlight Compensation	Support



Audio

Full-Frequency Speaker	96 dB SPL at 0.5 m
Microphone Array	Beamforming microphone with 6m pickup distance
Expansion MIC	Support (Optional)



USB Features

Type of Connection	USB 3.0, downward compatible with USB 2.0
Color System / Compression	MJPEG / YUY2
USB Audio	32K sampling rate, UAC 1.0 support
USB Video Communication Protocol	UVC 1.1
USB PTZ Control	Support

Others

Installation Method	Support desktop placement, wall-mounting and TV-mounting etc.
Supplied Cables	USB Cable
Safety Protection	Anti-theft lock

General Specifications

Power Supply	DC 12V, 2A (Max.)
Operating Temperature	0° C ~ 40° C
Storage Temperature	-40° C ~ 60° C
Dimension	600mm x 115mm x 135mm (with bracket)
Net weight	2.5 Kg

Interfaces

HD Output	1 x HDMI, Version 1.4b
USB Interface	1 x USB3.0, Type C; 1 x USB2.0, Type A
Wireless	Bluetooth data communication (Bluetooth 5.0)